




PRODUCT-DETAILS

DDA203 B S-63/0.3

DDA203 B S-63/0.3 Residual Current Device Block



| General Information | |
|-----------------------|--|
| Extended Product Type | DDA203 B S-63/0.3 |
| Product ID | 2CSB203892R3630 |
| EAN | 8012542733126 |
| Catalog Description | DDA203 B S-63/0.3 Residual Current Device Block |
| Long Description | The RCD block DDA200 series is suitable for assembly with MCBs S200 series and S300P. Type B is also sensitive to continuous current pulsating earth fault currents. They are used for protection in installations with electronic equipment according to EN 50178. Applications: tertiary and industrial. |

| Technical | |
|---|-------------------------------------|
| Standards | IEC/EN 61009 Ann. G IEC/EN 62423 |
| Type of Residual Current | Type B |
| Rated Voltage (U _r) | 400...400 V |
| Rated Operational Voltage | 400 V |
| Rated Insulation Voltage (U _i) | 500 V |
| Rated Impulse Withstand Voltage (U _{imp}) | 4 kV |

| | |
|---------------------------------|---|
| Rated Current (I _n) | 63 A |
| Rated Residual Current | 300 mA |
| Maximum Surge Current | 5 kA |
| Leakage Current Type | B |
| Rated Frequency (f) | 50 ... 60 Hz |
| Power Loss | 7.6 W |
| Power Supply Connection | Arbitrary |
| Electrical Endurance | 10000 cycle |
| Number of Poles | 3 |
| Operating Characteristic | Selective |
| Connecting Capacity | Rigid 25 ... 25 mm² Flexible 25 ... 25 mm² |

Material Compliance

| | |
|---|--|
| RoHS Information | 9AKK106713A5614 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 20070731 |
| REACH Declaration | 9AKK108467A9482 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

Environmental

| | |
|--|---|
| Ambient Temperature | -25...55 °C |
| Ambient Air Temperature | Operation -25...55 °C |
| Degree of Protection | IP2X |
| Resistance to Vibrations | 20 Cycles with Load 0.8 In: 1g or 1mm 50 ... 150 ... 5 Hz |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g 2 shocks 13 ms |
| Environmental Information | Refer to RoHS |

Technical UL/CSA

| | |
|-------------------------------------|---------------|
| Short-Circuit Current Rating (SCCR) | 0.3 ... 0.3 A |
|-------------------------------------|---------------|

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 122 mm |
| Product Net Height | 93 mm |
| Product Net Depth / Length | 76 mm |
| Product Net Weight | 0.318 kg |

Ordering

| | |
|------------------------------|-------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Gross Weight | 0.375 kg |

Certificates and Declarations



| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK106713A5615 |
|--------------------------------|-----------------|

| | |
|--------------------------|-----------------|
| Installation | |
| Instructions and Manuals | 9AKK108467A7092 |

| | |
|-----------------------------------|-----------------|
| Popular Downloads | |
| Data Sheet, Technical Information | 9AKK107991A8329 |

| | |
|----------------------------|--|
| Classifications | |
| ETIM 8 | EC002297 - Residual current circuit breaker (RCCB) module |
| ETIM 9 | EC002297 - Residual current circuit breaker (RCCB) module |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85363030 |
| eClass | V11.0 : 27142210 |
| Object Classification Code | F |

| | |
|--|--|
| Categories | |
| Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCD Blocks | |



360°