

PRODUCT-DETAILS

DDA802 A S-100/0.3 DDA802 A S-100/0.3 Residual Current Device Block



General Information	
Extended Product Type	DDA802 A S-100/0.3
Product ID	2CSB802201R3000
EAN	8012542542537
Catalog Description	DDA802 A S-100/0.3 Residual Current Device Block
Long Description	The RCD Block DDA800 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is particularly suitable for protection against earth fault currents with an intentional tripping delay, in order to realize selectivity with downstream instantaneous devices.

Technical	
Standards	IEC EN 60947-2 Ann. B
Type of Residual Current	Туре А
Suitable For	\$800S
	\$800N
	S800C
	S800B
Rated Voltage (Ur)	230 V AC
	240 V AC

© 2024 ABB. All rights reserved.

Subject to change without notice

	400 V AC
Rated Operational Voltage	400/690 V
Rated Insulation Voltage (Ui)	690 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Current (In)	100 A
Rated Residual Current	300 mA
Maximum Surge Current	5 kA
Leakage Current Type	A
Rated Frequency (f)	50 60 Hz
Power Loss	7 W
Number of Poles	2
Operating Characteristic	Selective
Connecting Capacity	Rigid 6 50 mm² Flexible 6 70 mm²

Material Compliance	
RoHS Information	9AKK106713A5616
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20110608
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Temperature	-2560 °C
Ambient Air Temperature	Operation -2560 °C
Degree of Protection	IP2X
Environmental Information	refer to RoHS information
Technical UL/CSA Short-Circuit Current Rating (SCCR)	0.3 0.3 A
Dimensions	
Width in Number of Modular Spacings	4.5
Product Net Width	81 mm

Product Net Depth /

Product Net Weight

Length

82.3 mm

0.300 kg

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.4 kg
Certificates and Declarations	
Declaration of Conformity - CE	9AKK106713A5616
Installation	
Instructions and Manuals	2CSB427001D0003
Popular Downloads	
Data Sheet, Technical Information	2CSC400002D0209
Classifications	
	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85363030
eClass	V11.0 : 27142210
Object Classification Code	F

Low Voltage Products and Systems \rightarrow Modular DIN Rail Products \rightarrow High Performance Circuit Breakers HPCBs \rightarrow High Performance Circuit Breakers HPCBs Accessories

