

PRODUCT-DETAILS

DDA802A-100/0.03 APR

DDA802A-100/0.03 APR Residual Current Device Block



General Information	
Extended Product Type	DDA802A-100/0.03 APR
Product ID	2CSB802401R1000
EAN	8012542544630
Catalog Description	DDA802A-100/0.03 APR Residual Current Device Block
Long Description	The RCD Block DDA800 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product provides the best compromise between safety and continuity in the service, thanks to the resistance to unwanted trippings. It is suitable for assembly with MCBs S800 series up to 100A.

Technical	
Standards	IEC EN 60947-2 Ann. B
Type of Residual Current	Type A
Suitable For	\$800S
	\$800N
	S800C
	S800B
Rated Voltage (U _r)	230 V AC

(CMRT)

	240 V AC
	400 V AC
Rated Operational Voltage	400/690 V
Rated Insulation Voltage (U _i)	690 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Current (In)	100 A
Rated Residual Current	30 mA
Maximum Surge Current	3 kA
Leakage Current Type	A
Rated Frequency (f)	50 60 Hz
Power Loss	7 W
Number of Poles	2
Operating Characteristic	Instantaneous (APR High Immunity)
Connecting Capacity	Rigid 6 50 mm² Flexible 6 70 mm²

Material Compliance	
RoHS Information	9AKK106713A5616
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20110608
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template	9AKK108468A3363

Environmental

Ambient Temperature -25...60 °C

Ambient Air Operation -25...60 °C

Temperature

Degree of Protection IP2X

Environmental refer to RoHS information

Technical UL/CSA	
Short-Circuit Current	0.03 0.03 A
Rating (SCCR)	

Dimensions	
Width in Number of Modular Spacings	4.5
Product Net Width	81 mm
Product Net Height	108.2 mm
Product Net Depth / Length	82.3 mm
Product Net Weight	0.300 kg

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross	0.4 kg

Certificates and Declarations	
Declaration of	9AKK106713A5616
Conformity - CE	

Installation	
Instructions and	2CSB427001D0003
Manuals	

Popular Downloads	
Data Sheet, Technical	2CSC400002D0209
Information	

Classifications	
ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85363030
eClass	V11.0:27142210
Object Classification Code	F

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow High\ Performance\ Circuit\ Breakers\ HPCBs\ \rightarrow High\ Performance\ Circuit\ Breakers\ HPCBs\ Accessories$





