

PRODUCT-DETAILS

## DDA804 A-100/0.5

# DDA804 A-100/0.5 Residual Current Device Block



| <b>General Information</b> |   |  |
|----------------------------|---|--|
| Extended Product Type      | DDA804 A-100/0.5  |  |
| Product ID                 | 2CSB804101R4000   |  |
| EAN                        | 8012542544937   |  |
| Catalog Description        | DDA804 A-100/0.5 Residual Current Device Block  |  |
| Long Description           | The RCD Block DDA800 series assures protection to people and installations against<br>fault current to earth. A large offer for standard instantaneous and selective AC and A<br>types is completed with some configurations for special applications. This product is<br>suitable for assembly with MCBs S800 series up to 100A. |  |

| Technical                |                       |
|--------------------------|-----------------------|
| Standards                | IEC EN 60947-2 Ann. B |
| Type of Residual Current | Туре А                |
| Suitable For             | \$800S                |
|                          | \$800N                |
|                          | \$800C                |
|                          | S800B                 |
| Rated Voltage (Ur)       | 230/400 V AC          |
|                          | 240/415 V AC          |
|                          | 400/690 V AC          |

© 2024 ABB. All rights reserved.

2024/04/12

Subject to change without notice

## DDA804 A-100/0.5

| Rated Operational<br>Voltage                              | 400/690 V                           |
|---|-------------------------------------|
| Rated Insulation Voltage<br>(Ui)                          | 690 V                               |
| Rated Impulse<br>Withstand Voltage (U <sub>imp</sub><br>) | 6 kV                                |
| Rated Current (I <sub>n</sub> )                           | 100 A                               |
| Rated Residual Current                                    | 500 mA                              |
| Maximum Surge Current                                     | 0.25 kA                             |
| Leakage Current Type                                      | A                                   |
| Rated Frequency (f)                                       | 50 60 Hz                            |
| Power Loss  | 10.5 W                              |
| Number of Poles   | 4                                   |
| Operating Characteristic                                  | Instantaneous                       |
| Connecting Capacity                                       | Rigid 6 50 mm²<br>Flexible 6 70 mm² |

| Material Compliance                               |   |
|---|---|
| RoHS Information                                  | 9AKK106713A5616   |
| RoHS Status                                       | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201 |
| RoHS Date   | 20110608  |
| REACH Declaration                                 | 9AKK108467A9482   |
| Conflict Minerals<br>Reporting Template<br>(CMRT) | 9AKK108468A3363   |
| Environmental                                     |   |
| Ambient Temperature                               | -2560 °C  |
| Ambient Air<br>Temperature                        | Operation -2560 °C  |
| Degree of Protection                              | IP2)  |
| Environmental<br>Information                      | refer to RoHS information   |
|   |   |
| Technical UL/CSA                                  |   |
| Short-Circuit Current<br>Rating (SCCR)            | 0.5 0.5 A   |
|   |   |
| Dimensions  |   |

| 6.5      |
|----------|
| 117 mm   |
| 108.2 mm |
| 82.3 mm  |
| 0.460 kg |
|          |

## Ordering

© 2024 ABB. All rights reserved.

| box 1 piece |
|-------------|
| 0.56 kg     |
|             |
|             |

### **Certificates and Declarations**

Declaration of Conformity - CE

#### Installation

Instructions and Manuals

#### **Popular Downloads**

Data Sheet, Technical Information

| 2 | CSC <sub>4</sub> | 10000 | 02D0 | 209 |
|---|------------------|-------|------|-----|

9AKK106713A5616

2CSB427001D0003

| Classifications                                       |  |  |
|---|--|--|
| ETIM 8  | EC002297 - Residual current circuit breaker (RCCB) module  |  |
| ETIM 9 EC002297 - Residual current circuit breaker (R |  |  |
| WEEE Category   | 5. Small Equipment (No External Dimension More Than 50 cm) |  |
| WEEE B2C / B2B  | Business To Business                                       |  |
| CN8   | 85363030   |  |
| eClass  | V11.0 : 27142210   |  |
| Object Classification                                 | F  |  |
| Code  |  |  |

#### Categories

Low Voltage Products and Systems  $\rightarrow$  Modular DIN Rail Products  $\rightarrow$  High Performance Circuit Breakers HPCBs  $\rightarrow$  High Performance Circuit Breakers HPCBs Accessories





4/4

© 2024 ABB. All rights reserved.

2024/04/12