DDA804A-100/0.03 APR 1/3



PRODUCT-DETAILS

## DDA804A-100/0.03 APR DDA804A-100/0.03 APR Residual Current Device Block



General Information	
Extended Product Type	DDA804A-100/0.03 APR
Product ID	2CSB804401R1000
EAN	8012542547136
Catalog Description	DDA804A-100/0.03 APR Residual Current Device Block
Long Description	The RCD Block DDA800 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product provides the best compromise between safety and continuity in the service, thanks to the resistance to unwanted trippings. It is suitable for assembly with MCBs S800 series up to 100A.

Technical	
Standards	IEC EN 60947-2 Ann. B
Type of Residual Current	Type A
Suitable For	\$800\$ \$800N \$800C \$800B
Rated Voltage (U <sub>r</sub> )	230/400 V AC 240/415 V AC 400/690 V AC
Rated Operational Voltage	400/690 V

DDA804A-100/0.03 APR 2/3

Rated Insulation Voltage (U <sub>i</sub> )	690 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	6 kV
Rated Current (I <sub>n</sub> )	100 A
Rated Residual Current	30 mA
Maximum Surge Current	3 kA
Leakage Current Type	A
Rated Frequency (f)	50 60 Hz
Power Loss	10.5 W
Number of Poles	4
Operating Characteristic	Instantaneous (APR High Immunity)
Connecting Capacity	Rigid 6 50 mm² Flexible 6 70 mm²
Material Compliance	
RoHS Information	9AKK106713A5616
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20110608
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Environmental	
Ambient Temperature	-2560 °C
Ambient Air Temperature	Operation -2560 °C
Degree of Protection	IP2X
Environmental Information	refer to RoHS information
Technical UL/CSA	
Short-Circuit Current Rating (SCCR)	0.03 0.03 A
Having (CCCTV)	
Dimensions	
Width in Number of	6.5
Modular Spacings Product Not Width	117 mm
Product Not Hoight	108.2 mm
Product Net Height Product Net Depth /	82.3 mm
Length	02.3 11111
Product Net Weight	0.460 kg
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.56 kg
Certificates and Declarations	

Declaration of Conformity

9AKK106713A5616

- CE

Installation	
Instructions and Manuals	2CSB427001D0003

Popular Downloads	
Data Sheet, Technical	2CSC400002D0209

Classifications	
ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85363030
eClass	V11.0 : 27142210
Object Classification Code	<u> </u>

## Categories

 $Low\ Voltage\ Products\ \to\ High\ Performance\ Circuit\ Breakers\ HPCBs\ \to\ High\ Performance\ Circuit\ Breakers\ HPCBs\ \to\ High\ Performance\ Circuit\ Breakers\ HPCBs\ Accessories$ 





