DDA804 A-100/0.3



PRODUCT-DETAILS

## DDA804 A-100/0.3 DDA804 A-100/0.3 Residual Current Device Block



| General Information   |  |
|-----------------------|--|
| Extended Product Type | DDA804 A-100/0.3   |
| Product ID            | 2CSB804101R3000  |
| EAN                   | 8012542547532  |
| Catalog Description   | DDA804 A-100/0.3 Residual Current Device Block   |
| Long Description      | The RCD Block DDA800 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is suitable for assembly with MCBs S800 series up to 100A. |

| Technical                       |  |
|---------------------------------|--|
| Standards                       | IEC EN 60947-2 Ann. B                        |
| Type of Residual Current        | Type A                                       |
| Suitable For                    | \$800\$<br>\$800N<br>\$800C<br>\$800B        |
| Rated Voltage (U <sub>r</sub> ) | 230/400 V AC<br>240/415 V AC<br>400/690 V AC |
| Rated Operational Voltage       | 400/690 V                                    |

DDA804 A-100/0.3 2/3

| Rated Insulation Voltage (U <sub>i</sub> )          | 690 V  |
|---|--|
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 6 kV   |
| Rated Current (I <sub>n</sub> )                     | 100 A  |
| Rated Residual Current                              | 300 mA   |
| Maximum Surge Current                               | 0.25 kA  |
| Leakage Current Type                                | A  |
| Rated Frequency (f)                                 | 50 60 Hz   |
| Power Loss  | 10.5 W   |
| Number of Poles                                     | 4  |
| Operating Characteristic                            | Instantaneous  |
| Connecting Capacity                                 | Rigid 6 50 mm²<br>Flexible 6 70 mm²                                    |
|   |  |
| Material Compliance                                 |  |
| RoHS Information                                    | 9AKK106713A5616  |
| RoHS Status   | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date   | 20110608   |
| REACH Declaration                                   | 9AKK108467A9482  |
| Conflict Minerals Reporting Template (CMRT)         | 9AKK108468A3363  |
|   |  |
| Environmental                                       |  |
| Ambient Temperature                                 | -2560 °C   |
| Ambient Air Temperature                             | Operation -2560 °C   |
| Degree of Protection                                | IP2X   |
| Environmental Information                           | refer to RoHS information  |
| Technical UL/CSA                                    |  |
| Short-Circuit Current<br>Rating (SCCR)              | 0.3 0.3 A  |
|   |  |
| Dimensions  |  |
| Width in Number of                                  | 6.5  |
| Modular Spacings Product Net Width                  | 117 mm   |
| Product Net Height                                  | 108.2 mm   |
| Product Net Depth /                                 | 82.3 mm  |
| Length  | 02.3 11111   |
| Product Net Weight                                  | 0.460 kg   |
| Ordering  |  |
|   | L 4  |
| Package Level 1 Units                               | box 1 piece  |
| Package Level 1 Gross<br>Weight                     | 0.56 kg  |
| Certificates and Declarations                       |  |

DDA804 A-100/0.3 3/3

<u>- CE</u>

| Installation             |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 2CSB427001D0003 |

## Popular Downloads Data Sheet, Technical 2CSC400002D0209 Information

| Classifications                       |  |
|---------------------------------------|--|
| ETIM 8                                | EC002297 - Residual current circuit breaker (RCCB) module  |
| ETIM 9                                | EC002297 - Residual current circuit breaker (RCCB) module  |
| WEEE Category                         | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B                        | Business To Business                                       |
| CN8                                   | 85363030   |
| UNSPSC                                | 39121601   |
| eClass                                | V11.0 : 27142210   |
| IDEA Granular Category<br>Code (IGCC) | 4875 >> Residual current circuit breaker (RCCB)            |
| Object Classification Code            | <u>F</u>   |

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow High\ Performance\ Circuit\ Breakers\ HPCBs\ \rightarrow High\ Performance\ Circuit\ Breakers\ HPCBs\ Accessories$ 





