

PRODUCT-DETAILS

DDA202 AC-40/0.5 DDA202 AC-40/0.5 Residual Current Device Block



General Information	
Extended Product Type	DDA202 AC-40/0.5
Product ID	2CSB202001R4400
EAN	8012542792109
Catalog Description	DDA202 AC-40/0.5 Residual Current Device Block
Long Description	The RCD block DDA200 series is suitable for assembly with MCBs S200 series and S300P. It assures protection against the effects of sinusoidal alternating earth fault currents, protection, against indirects contacts and additional protection against direct (with sensitivity = 30 mA) contacts. Applications: residential, commercial, industrial.

Technical		
Standards	IEC/EN 61009 Ann. G	
Type of Residual Current	Type AC	
Rated Voltage (U _r)	230/400 V	
Rated Operational Voltage	230 V	
Rated Insulation Voltage (U_i)	500 V	
Rated Impulse Withstand Voltage (U _{imp})	4 kV	
Rated Current (I _n)	40 A	

DDA202 AC-40/0.5

Rated Residual Current	500 mA	
Leakage Current Type	AC	
Rated Frequency (f)	50 60 Hz	
Power Loss	3.2 W	
Power Supply Connection	Arbitrary	
Electrical Endurance	10000 cycle	
Number of Poles	2	
Operating Characteristic	Instantaneous	
Options Provided		
Connecting Capacity	Rigid 25 25 mm ²	
	Flexible 25 25 mm ²	
Material Compliance		
RoHS Information	9AKK106713A5614	
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
RoHS Date		
	20070731 0AKK108467A0482	
REACH Declaration	9AKK108467A9482	
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363	
Environmental		
	25 55 00	
Ambient Temperature	-2555 °C	
Ambient Air Temperature	Operation -2555 °C	
Degree of Protection	IP2X	
Resistance to Vibrations	20 Cycles with Load 0.8 In: 1g or 1mm 50 150 5 Hz	
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms	
Environmental Information	Refer to RoHS	
Technical UL/CSA		
Short-Circuit Current Rating (SCCR)	0.5 0.5 A	
Dimensions		
Product Net Width	70 mm	
Product Net Height	93 mm	
Product Net Depth / Length	76 mm	
Product Net Weight	0.210 kg	
Ordering		
Package Level 1 Units	box 1 piece	
Package Level 1 Gross Weight	0.245 kg	
Certificates and Declarations		
	0AZZZ106740AF644	
Declaration of Conformity - CE	9AKK106713A5614	

DDA202 AC-40/0.5 3/3

Installation	
Instructions and Manuals	9AKK108467A7091
Popular Downloads	
Data Sheet, Technical	9AKK107991A8329
Information	
Classifications	
ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
	Business To Consumer
WEEE B2C / B2B	Business to Consumer
WEEE B2C / B2B CN8	85363030

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Residual\ Current\ Devices\ RCDs\ \rightarrow\ Residual\ Current\ Devices\ RCD\ Blocks$

