




PRODUCT-DETAILS

DDA204 A S-63/1

DDA204 A S-63/1 Residual Current Device Block



General Information	
Extended Product Type	DDA204 A S-63/1
Product ID	2CSB204201R5630
EAN	8012542800408
Catalog Description	DDA204 A S-63/1 Residual Current Device Block
Long Description	The RCD block DDA200 series is suitable for assembly with MCBs S200 series and S300P. It assures protection against the effects of sinusoidal alternating and direct pulsating earth fault currents with an intentional tripping delay, in order to realize the selectivity with downstream instantaneous devices. Applications: commercial, industrial.

Technical	
Standards	IEC/EN 61009 Ann. G
Type of Residual Current	Type A
Rated Voltage (U _r)	230/400 V
Rated Operational Voltage	230/400 V
Rated Insulation Voltage (U _i)	500 V

Rated Impulse Withstand Voltage (U _{imp})	4 kV
Rated Current (I _n)	63 A
Rated Residual Current	1000 mA
Maximum Surge Current	5 kA
Leakage Current Type	A
Rated Frequency (f)	50 ... 60 Hz
Power Loss	7.6 W
Power Supply Connection	Arbitrary
Electrical Endurance	10000 cycle
Number of Poles	4
Operating Characteristic	Selective
Options Provided	-
Connecting Capacity	Rigid 25 ... 25 mm ² Flexible 25 ... 25 mm ²

Material Compliance

RoHS Information	9AKK106713A5614
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20070731
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Temperature	-25...55 °C
Ambient Air Temperature	Operation -25...55 °C
Degree of Protection	IP2X
Resistance to Vibrations	20 Cycles with Load 0.8 In: 1g or 1mm 50 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27	25g 2 shocks 13 ms
Environmental Information	Refer to RoHS

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	1...1 A
--	---------

Dimensions

Product Net Width	140 mm
Product Net Height	93 mm
Product Net Depth / Length	76 mm
Product Net Weight	0.311 kg

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	378 g

Certificates and Declarations	
Declaration of Conformity - CE	9AKK106713A5614

Installation	
Instructions and Manuals	9AKK108467A7091

Popular Downloads	
Data Sheet, Technical Information	9AKK107991A8329

Classifications	
ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142210
Object Classification Code	F

Categories	
Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCD Blocks	

