DDA802AC-63/0.3



PRODUCT-DETAILS

DDA802AC-63/0.3

DDA802AC-63/0.3 Residual Current Device Block



General Information	
Extended Product Type	DDA802AC-63/0.3
Product ID	2CSB802001R3630
EAN	8012542919902
Catalog Description	DDA802AC-63/0.3 Residual Current Device Block
Long Description	The RCD Block DDA800 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is suitable for assembly with MCBs S800 series up to 63A.

Technical	
Standards	IEC EN 60947-2 Ann. B
Type of Residual Current	Type AC
Suitable For	S800S
	\$800N
	S800C
	S800B
Rated Voltage (U _r)	230 V AC
	240 V AC
	400 V AC

DDA802AC-63/0.3 2/4

Rated Operational Voltage	400/690 V
Rated Insulation Voltage (U _i)	690 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Current (In)	63 A
Rated Residual Current	300 mA
Maximum Surge Current	0.25 kA
Leakage Current Type	AC
Rated Frequency (f)	50/60 Hz
Power Loss	9 W
Number of Poles	2
Operating Characteristic	Instantaneous
Options Provided	-
Connecting Capacity	Rigid 6 50 mm² Flexible 6 70 mm²

Material Compliance	
RoHS Information	9AKK106713A5616
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20110608
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	b2c01131-e327-4cd6-b9d9-5f4b6da9ae73 Italy (IT)

Environmental	
Ambient Temperature	-2560 °C
Ambient Air Temperature	Operation -2560 °C
Degree of Protection	IP2X
Environmental Information	document not needed

Technical UL/CSA	
Short-Circuit Current	0.3 0.3 A
Rating (SCCR)	

Dimensions	
Width in Number of Modular Spacings	4.5
Product Net Width	81 mm
Product Net Height	108.2 mm
Product Net Depth / Length	82.3 mm
Product Net Weight	0.300 kg

DDA802AC-63/0.3 3/4

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross	0.4 kg

Certificates and Declarations	
Declaration of	9AKK106713A5616
Conformity - CE	

Installation	
Instructions and	2CSB427001D0003
Manuals	

Popular Downloads	
Data Sheet, Technical	2CSC400002D0209
Information	

Classifications	
ETIM 8	EC002297 - Residual current circuit breaker (RCCB) module
ETIM 9	EC002297 - Residual current circuit breaker (RCCB) module
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85363030
eClass	V11.0 : 27142210
Object Classification Code	F

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow High\ Performance\ Circuit\ Breakers\ HPCBs\ \rightarrow High\ Performance\ Circuit\ Breakers\ HPCBs\ Accessories$

DDA802AC-63/0.3 4/4









3605