




PRODUCT-DETAILS

BEA16-4KF

BEA16-4KF Connecting Link with Manual Motor Starter



General Information	
Extended Product Type	BEA16-4KF
Product ID	1SBN081325T1000
EAN	3471523019034
Catalog Description	BEA16-4KF Connecting Link with Manual Motor Starter
Long Description	<p>BEA16-4KF is an insulated 3-pole connecting link used to connect AF09..K ... AF16..K or AFC09..K ... AFC16..K contactors with the MS132-K manual motor starters. The BEA16-4KF ensures the electrical and mechanical connection between the contactor or reversing contactors and the associated manual motor starter. Black fork pieces help for a quick dismounting of the DOL starter.</p> <p>With the Push-in Spring terminals, one push is all you need for a faster than ever installation, an easier than ever wiring and a reliable as ever connection.</p>

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	85389099

Popular Downloads

Instructions and Manuals	1SBC101065M6801
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	90 mm
Product Net Height	32.5 mm
Product Net Weight	0.044 kg

Technical

Standards	UL 60947-4-1, CSA C22.2 No. 60947-4-1
Rated Operational Voltage	Main Circuit 690 V AC
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Terminal Type	Push-in Spring Terminals
Suitable For	MS132 AF09 AF09Z AF12 AF12Z AF16 AF16Z AFC09 AFC12 AFC16

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

Declaration of Conformity - CE	1SBD250021U1000
Declaration of Conformity - UKCA	1SBD250043U1000
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
UL Certificate	UL-US-L312527-151-12119002-5 UL-CA-L312527-451-12119002-5

Container Information

Package Level 1 Units	box 10 piece
Package Level 1 Width	92 mm

Package Level 1 Depth / Length	225 mm
Package Level 1 Height	80 mm
Package Level 1 Gross Weight	0.56 kg
Package Level 1 EAN	3471523019034
Package Level 3 Units	840 piece

Classifications

ETIM 6	EC002498 - Accessories for low-voltage switch technology
ETIM 7	EC002498 - Accessories for low-voltage switch technology
ETIM 8	EC002498 - Accessories/spare parts for low-voltage switch technology
eClass	V11.0 : 27371392
UNSPSC	39120000
E-Number (Finland)	3709779

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

