



PRODUCT-DETAILS

BETR020202

EX T PIECE FITTING NC12X12X12 BLK



Product image
not available

| General Information | |
|-----------------------|--|
| Extended Product Type | BETR020202 |
| Product ID | 7TCA297120R0381 |
| EAN | 5011949240278 |
| Catalog Description | EX T PIECE FITTING NC12X12X12 BLK |
| Long Description | Splice Connector for Conduit, T-Shape with Internal Female Thread, 3 Ends with Conduit Size 12mm/NW10, IP68 Rating, Approved for Zones 1, 2, 21, 22, Modified Nylon 12 with Nickel Plated Threads, Black |

| Additional Information | |
|------------------------|--|
| Application | For Indoor and Outdoor Applications for Zones 1, 2, 21, 22 |
| Product Type | T-Shaped Splice Connector |

| Ordering | |
|----------|---------------|
| EAN | 5011949240278 |

| Dimensions | |
|----------------------------|-------|
| Product Net Depth / Length | 59 mm |

| Technical | |
|---------------------|--|
| Number of Batteries | 0 |
| Color | Black |
| Material | Modified Nylon/Polyamide 12 with Nickel Plated Threads |
| Size | 3 Ends with Conduit Size 12mm/NW10 |

| Environmental | |
|---------------|---------------------------|
| WEEE Category | Product Not in WEEE Scope |

| Container Information | |
|--------------------------------|-------------------|
| Package Level 1 Units | 10 piece |
| Package Level 1 Height | 7.9 in 201 mm |
| Package Level 1 Depth / Length | 8.3 in 211 mm |
| Package Level 1 Width | 11.9 in 302 mm |

| Certificates and Declarations | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK106930A7736 |
| Instructions and Manuals | BETR020202 |
| Declaration of Conformity - CE | 9AKK107680A0674 |

| Classifications | |
|-----------------|---|
| ETIM 8 | EC001172 - Coupler for corrugated plastic hoses |
| UNSPSC | 39131717 |

| Categories | |
|------------|--|
|------------|--|

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems



Product image
not available