



PRODUCT-DETAILS

CA4-04MK

CA4-04MK Auxiliary Contact Block



General Information	
Extended Product Type	CA4-04MK
Product ID	1SBN010146R1104
EAN	3471523131330
Catalog Description	CA4-04MK Auxiliary Contact Block
Long Description	CA4-04MK is a 4-pole front mounted auxiliary contact block equipped with Push-In Spring terminals. CA4-..M version offers terminal assortment matching the marking of 3-pole AF(C) 09..16(Z)(B)-30-10 contactors. CA4-04MK is available with 4 N.C. instantaneous contacts for standard industrial environments. With the Push-in Spring terminals, one push is all you need for a faster than ever installation, an easier than ever wiring and a reliable as ever connection.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Popular Downloads	
Instructions and Manuals	1SBC101054M6801
CAD Dimensional	2CDC001079B0201

Drawing

Dimensions

Product Net Width	43 mm
Product Net Depth / Length	39.5 mm
Product Net Height	45 mm
Product Net Weight	0.05 kg

Technical

Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	4
Standards	IEC/EN 60947-5-1, UL 60947-5-1, CSA C22.2 No. 60947-5-1-14
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-5-1, $\Theta = 40\text{ °C}$ 16 A
Rated Operational Current AC-15 (I_{θ})	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 0.1 s 140 A for 1 s 100 A
Maximum Electrical Switching Frequency	(AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour
Rated Operational Current DC-13 (I_{θ})	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Insulation Voltage (U_i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Maximum Mechanical Switching Frequency	3600 cycles per hour
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.5 ... 2.5 mm ² Flexible with Insulated Ferrule 1/2x 0.5 ... 1.5 mm ² Flexible 1/2x 0.5 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ²
Wire Stripping Length	Auxiliary Circuit 10 mm
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Terminal Type	Push-in Spring Terminals
Suitable For	AF09 AF09Z AF12 AF12Z AF16 AF16Z AFC09 AFC12 AFC16 AF09B AF09ZB AF12B AF12ZB

AF16B
AF16ZB

Technical UL/CSA

Connecting Capacity Rigid Solid 1/2x 18-14 AWG
Auxiliary Circuit UL/CSA

Material Compliance

Conflict Minerals 9AKK108467A5658
Reporting Template (CMRT)
REACH Declaration 2CMT2021-006202
RoHS Information 2CMT2021-006277
RoHS Status Following EU Directive 2011/65/EU
WEEE B2C / B2B Business To Business
WEEE Category 5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

ABS Certificate ABS_20-2060694-PDA
CB Certificate CB_SE-93052A1
CQC Certificate CQC2011010304496319
CQC2013010304651497
Declaration of Conformity - CCC 2020980304001258
2020980304001259
Declaration of Conformity - CE 1SBD250007U1000
Declaration of Conformity - UKCA 1SBD250038U1000
DNV Certificate DNV_TAE00001BV-5
LR Certificate LRS_LR23403517TA-02
RMRS Certificate RMRS_1802703280
UL Certificate UL-US-L252354-131-82119002-6
UL-CA-L252354-331-82119002-5

Container Information

Package Level 1 Units box 1 piece
Package Level 1 Width 46 mm
Package Level 1 Depth / Length 46 mm
Package Level 1 Height 46 mm
Package Level 1 Gross Weight 0.05 kg
Package Level 1 EAN 3471523131330

Classifications

Object Classification Code K
ETIM 4 EC002498 - Accessories for low-voltage switch technology
ETIM 5 EC002498 - Accessories for low-voltage switch technology
ETIM 6 EC000041 - Auxiliary contact block
ETIM 7 EC000041 - Auxiliary contact block
ETIM 8 EC000041 - Auxiliary contact block
eClass V11.0 : 27371302
UNSPSC 39121522

IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block
E-Number (Finland)	3708032
E-Number (Sweden)	3210651

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

