



PRODUCT-DETAILS

CE5-01W2

CE5-01W2 Auxiliary Contact Block



General Information	
Extended Product Type	CE5-01W2
Product ID	1SBN010018R1001
EAN	3471522199515
Catalog Description	CE5-01W2 Auxiliary Contact Block
Long Description	CE5-01W2 is a 1-pole front mounted auxiliary contact block equipped with screw terminals and can be fitted on AF09(Z)...96, A9...75, AFC09...38, AL9...AE75, AX9...AX80 contactors and NF(C)(Z), N, NL, NX contactor relays. CE5-01W2 is used for the operation of auxiliary circuits and control circuits for severe industrial environments. CE5-01W2 is available with 1 N.C. including a built-in microswitch IP67, degree of protection (IP20 on terminals), defined for a 2 A AC-15 24-240 V 50/60 Hz / DC-12 24 V DC.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Popular Downloads	
Instructions and Manuals	1SBC101013M5501
CAD Dimensional	2CDC001079B0201

Drawing

Dimensions

Product Net Width	9.8 mm
Product Net Depth / Length	32.5 mm
Product Net Height	46.8 mm
Product Net Weight	0.02 kg

Technical

Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	1
Standards	IEC/EN 60947-5-1
Rated Operational Voltage	Auxiliary Circuit 250 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Operational Current AC-15 (I _θ)	(24 / 127 V) 2 A (220 / 240 V) 2 A
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 250 V
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 4 mm ² Rigid Stranded 1/2x 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP67
Terminal Type	Screw Terminals
Suitable For	AF09 AF09Z AF12 AF12Z AF16 AF16Z AF26 AF26Z AF30 AF30Z AF38 AF38Z AF40 AF52 AF65 AF80 AF96 AFC09 AFC12 AFC16 AFC26 AFC30 AFC38 NF22E NFZ22E NF31E NFZ31E NF40E NFZ40E NFC22E NFC31E NFC40E A9 A12 A16 A26 A30 A40 A50 A63 A75 A95

A110
AL9
AL9Z
AL12
AL12Z
AL16
AL16Z
AL26
AL30
AL40
AE45
AE50
AE63
AE75
N22E
N31E
N40E
NL31E
NLZ31E
NL40E
NLZ40E
AX06
AX09
AX12
AX18
AX25
AX32
AX40
AX50
AX65
AX80
NX22E
NX31E
NX40E

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CB_SE-94569
CQC Certificate	CQC2011010304466171
Declaration of Conformity - CCC	2020980304001286
Declaration of Conformity - CE	1SBD250817U1000
Declaration of Conformity - UKCA	1SBD250834U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
GOST Certificate	GOST_POCCFRME77B07175
RINA Certificate	RINA_ELE172319XG001

Container Information

Package Level 1 Units	blister 1 piece
Package Level 1 Width	100 mm
Package Level 1 Depth / Length	100 mm
Package Level 1 Height	10 mm

Package Level 1 Gross Weight	0.02 kg
Package Level 1 EAN	3471522199515
Package Level 2 Units	box 126 piece
Package Level 2 Width	245 mm
Package Level 2 Depth / Length	75 mm
Package Level 2 Height	153 mm
Package Level 2 Gross Weight	2.52 kg
Package Level 3 Units	4536 piece

Classifications

Object Classification Code	K
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
IDEA Granular Category Code (IGCC)	4743 >> Auxiliary contact block

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

