



PRODUCT-DETAILS

CM-ENS.11P

CM-ENS.11P Liquid level monitoring relay 1c/o,
sensitivity 5-100kOhm



General Information	
Extended Product Type	CM-ENS.11P
Product ID	1SVR740850R0100
EAN	4013614502873
Catalog Description	CM-ENS.11P Liquid level monitoring relay 1c/o, sensitivity 5-100kOhm
Long Description	The CM-ENS.11P belongs to the CM liquid level monitoring relay range. It operates with a rated control supply voltage of 24 - 240 V AC/DC and has a 1 c/o (SPDT) output with contacts rated at 250 V / 4 A. It monitors liquid levels of conductive fluids and protects pumps against dry running or tanks against overflow and works according to the open-circuit principle. The sensitivity can be selected via front-face potentiometers. Several electrodes and a sealable transparent cover for protection against unauthorized changes are available as accessory. The device offers maintenance free Easy Connect Technology with push-in terminals.

Ordering	
EAN	4013614502873
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC112228D0201
Instructions and Manuals	1SVC730680M1001 1SVC730680M0001
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.117 kg

Technical

Function	Filling or draining monitoring
Number of Electrodes	3
Measuring Range	5 ... 100 kΩ
Rated Control Supply Voltage (U _s)	24 ... 240 V AC/DC
Rated Frequency (f)	Supply Circuit 50/60 Hz
Output	1 c/o (SPDT) contact
Terminal Type	Screwless Terminals
Rated Operational Current AC-12 (I _e)	(230 V) 4 A
Rated Operational Current AC-15 (I _e)	(230 V) 3 A
Rated Operational Current DC-12 (I _e)	(24 V) 4 A
Rated Operational Current DC-13 (I _e)	(24 V) 2 A
Minimum Switching Capacity	12 V 10 mA
Rated Impulse Withstand Voltage (U _{imp})	Measuring Circuit / Output Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 4 kV Supply Circuit / Output Circuit 4 kV
Rated Insulation Voltage (U _i)	Measuring Circuit / Output Circuit 300 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	1000000 cycle
Connecting Capacity	Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Tightening Torque	Control Circuit 0.9 N·m Main Circuit 1 N·m

Wire Stripping Length	8 mm
	Main Circuit 10 mm
Mounting Position	1 ... 5
	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14
	IEC/EN 63000
	IEC/EN 60255-27
	IEC/EN 61000-6-2
	IEC/EN 61000-6-3
	UL 508

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG
	Rigid 2x 20-16 AWG
Pilot Duty UL/CSA	B300

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C
	Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SVD981001-4501
RoHS Information	1SVD981001-4401
RoHS Status	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	2CMT2023-006536

Circular Value

End of Life Instructions	1SAC200290H0001
--------------------------	-----------------

Certificates and Declarations

CQC Certificate	CQC2015010303819793
cULus Certificate	cULus508_20150627-E140448
Declaration of Conformity - CCC	2020980303000198
Declaration of Conformity - CE	1SVD981005-00
Declaration of Conformity - UKCA	1SVD981005-10
DNV GL Certificate	DNV_GL_TAA00000RW

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.142 kg
Package Level 1 EAN	4013614502873

Classifications	
Object Classification Code	B
ETIM 7	EC001447 - (Fill) level monitoring relay
ETIM 8	EC001447 - (Fill) level monitoring relay
ETIM 9	EC001447 - (Fill) level monitoring relay
eClass	V11.0 : 27371813
UNSPSC	39122331
E-Number (Finland)	2712571

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Liquid Level Monitors and Controls → CM-Enx

