



PRODUCT-DETAILS

CM-ENS.13S

CM-ENS.13S Liquid level monitoring relay  
1c/o, sensitivity 5-100kOhm



General Information	
Extended Product Type	CM-ENS.13S
Product ID	1SVR730850R2100
EAN	4013614502903
Catalog Description	CM-ENS.13S Liquid level monitoring relay 1c/o, sensitivity 5-100kOhm
Long Description	The CM-ENS.13S belongs to the CM liquid level monitoring relay range. It operates with a rated control supply voltage of 110-130 V AC and 220-240 V AC and has a 1 c/o (SPDT) output with contacts rated at 250 V / 4 A. It monitors liquid levels of conductive fluids and protects pumps against dry running or tanks against overflow and works according to the open-circuit principle. The sensitivity can be selected via front-face potentiometers. Several electrodes and a sealable transparent cover for protection against unauthorized changes are available as accessory. The device offers screw connection technology with double-chamber cage connection terminals.

Ordering	
EAN	4013614502903
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

## Popular Downloads

Data Sheet, Technical Information	2CDC112228D0201
Instructions and Manuals	1SVC730680M1001 1SVC730680M0001
CAD Dimensional Drawing	2CDC001079B0201

## Dimensions

Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.153 kg

## Technical

Function	Filling or draining monitoring
Number of Electrodes	3
Measuring Range	5 ... 100 kΩ
Rated Control Supply Voltage (U <sub>s</sub> )	110 ... 130 V AC 220 ... 240 V AC
Rated Frequency (f)	Supply Circuit 50/60 Hz
Output	1 c/o (SPDT) contact
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I <sub>e</sub> )	(230 V) 4 A
Rated Operational Current AC-15 (I <sub>e</sub> )	(230 V) 3 A
Rated Operational Current DC-12 (I <sub>e</sub> )	(24 V) 4 A
Rated Operational Current DC-13 (I <sub>e</sub> )	(24 V) 2 A
Minimum Switching Capacity	12 V 10 mA
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	Measuring Circuit / Output Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV Supply Circuit / Measuring Circuit 4 kV Supply Circuit / Output Circuit 4 kV
Rated Insulation Voltage (U <sub>i</sub> )	Measuring Circuit / Output Circuit 300 V Output Circuit 1 / Output Circuit 2 300 V Supply Circuit / Measuring Circuit 300 V Supply Circuit / Output Circuit 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	1000000 cycle
Connecting Capacity	Flexible with Ferrule 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible with Ferrule 2x 0.5 ... 1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm <sup>2</sup> Flexible 1x 0.5 ... 2.5 mm <sup>2</sup> Flexible 2x 0.5 ... 1.5 mm <sup>2</sup>

	Rigid 1x 0.5 ... 4 mm <sup>2</sup> Rigid 2x 0.5 ... 2.5 mm <sup>2</sup>
Tightening Torque	0.6 ... 0.8 N·m Control Circuit 0.9 N·m Main Circuit 1 N·m
Wire Stripping Length	8 mm Main Circuit 10 mm
Recommended Screw Driver	0.8 x 4 4.5 Pozidriv 1
Mounting Position	1 ... 5 1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 1x 18-14 AWG Flexible 2x 18-16 AWG Rigid 1x 20-12 AWG Rigid 2x 20-14 AWG
Tightening Torque UL/CSA	7.08 in·lb
Pilot Duty UL/CSA	B300

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SVD981001-4501
RoHS Information	1SVD981001-4401
RoHS Status	Following EU Directive 2011/65/EU
Toxic Substances Control Act - TSCA	2CMT2023-006536

Circular Value

End of Life Instructions	1SAC200290H0001
--------------------------	-----------------

Certificates and Declarations

CQC Certificate	CQC2015010303819793
cULus Certificate	cULus508_20150627-E140448
Declaration of Conformity - CCC	2020980303000198
Declaration of Conformity - CE	1SVD981005-00
Declaration of Conformity - UKCA	1SVD981005-10
DNV GL Certificate	DNV_GL_TAA00000RW

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.177 kg
Package Level 1 EAN	4013614502903

Classifications

Object Classification Code	B
ETIM 7	EC001447 - (Fill) level monitoring relay
ETIM 8	EC001447 - (Fill) level monitoring relay
ETIM 9	EC001447 - (Fill) level monitoring relay
eClass	V11.0 : 27371813
UNSPSC	39122331
E-Number (Finland)	2712569

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Liquid Level Monitors and Controls → CM-Enx

