CPS10G-50-CV0 1/3



PRODUCT-DETAILS

CPS10G-50-CV0GREY SLEEVE CONF. VO, 50M



General Information	
Extended Product Type	CPS10G-50-CV0
Product ID	7TCG054800R0013
EAN	5414363406891
Catalog Description	GREY SLEEVE CONF. V0, 50M
Long Description	Flame Retardant Braided Sleeve, Gray Polyester for Temperatures -50 Degrees Celsius (-58 F) up to 150 Celsius (302 F), Nominal Diameter 10mm (0.394 Inches), Expandable Diameter Range 9mm (0.354 Inches) to 15mm (0.590 Inches), Mini-Reel Length 50m (164.04 Feet)

Ordering	
EAN	5414363406891
UPC	786209889300
Country of Origin	France (FR)
Selling Unit of Measure	roll

Dimensions

CPS10G-50-CV0 2/3

Product Net Depth / $$164.04\,\mathrm{ft}$$ Length $$50\,\mathrm{m}$$

Container Information	
Package Level 1 Units	1 reel
Package Level 1 Width	6.7 in 170 mm
Package Level 1 Height	4.33 in 110 mm
Package Level 1 Depth / Length	6.7 in 170 mm
Package Level 2 Units	5 reel
Package Level 2 Width	14.76 in 375 mm
Package Level 2 Height	13.78 in 350 mm
Package Level 2 Depth / Length	29.53 in 750 mm

Additional Information	
Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Gray
Effective Date	20071010
Material	Polyester
Product Name	OTHER BRAIDED SLEEVING
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F -50 to 150 °C

Certificates and Declarations		
Data Sheet, Technical Information	CPS10G-50-CV0	

Classifications		
ETIM 6	EC001937 - Cable protection for installation duct	
ETIM 7	EC001937 - Cable protection for installation duct	
ETIM 8	EC001937 - Cable protection for installation duct	
UNSPSC	39131602	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving	

CPS10G-50-CV0 3/3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$

