



PRODUCT-DETAILS

CPS15G-50-CV0
GREY SLEEVING CONF. V0, 50M



General Information	
Extended Product Type	CPS15G-50-CV0
Product ID	7TCG054800R0029
EAN	5414363406907
Catalog Description	GREY SLEEVING CONF. V0, 50M
Long Description	Flame Retardant Braided Sleeve, Gray Polyester for Temperatures -50 Degrees Celsius (-58 F) up to 150 Celsius (302 F), Nominal Diameter 15mm (0.590 Inches), Expandable Diameter Range 13mm (0.512 Inches) to 20mm (0.787 Inches), Mini-Reel Length 50m (164.04 Feet)

Ordering	
EAN	5414363406907
UPC	786209889324
Country of Origin	France (FR)
Selling Unit of Measure	roll

Dimensions	
Product Net Depth / Length	164.04 ft 50 m

Container Information	
Package Level 1 Units	1 reel
Package Level 1 Width	7.08 in 180 mm
Package Level 1 Height	4.33 in 110 mm
Package Level 1 Depth / Length	7.08 in 180 mm
Package Level 2 Units	5 reel
Package Level 2 Width	14.76 in 375 mm
Package Level 2 Height	13.58 in 345 mm
Package Level 2 Depth / Length	29.53 in 750 mm

Additional Information	
Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Gray
Effective Date	20071010
Material	Polyester
Product Name	OTHER BRAIDED SLEEVING
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F -50 to 150 °C

Certificates and Declarations	
Data Sheet, Technical Information	CPS15G-50-CV0

Classifications	
ETIM 6	EC001937 - Cable protection for installation duct
ETIM 7	EC001937 - Cable protection for installation duct
ETIM 8	EC001937 - Cable protection for installation duct
UNSPSC	39131602
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

