CPS20G-50-CV0 1/3



PRODUCT-DETAILS

## **CPS20G-50-CV0**GREY BRD SLEEVE CONF. VO, 50M



General Information	
Extended Product Type	CPS20G-50-CV0
Product ID	7TCG054800R0039
EAN	5414363406914
Catalog Description	GREY BRD SLEEVE CONF. V0, 50M
Long Description	Flame Retardant Braided Sleeve, Gray Polyester for Temperatures -50 Degrees Celsius (-58 F) up to 150 Celsius (302 F), Nominal Diameter 20mm (0.787 Inches), Expandable Diameter Range 18mm (0.709 Inches) to 25mm (0.984 Inches), Mini-Reel Length 50m (164.04 Feet)

Ordering	
EAN	5414363406914
UPC	786209889348
Country of Origin	France (FR)
Selling Unit of Measure	roll

## **Dimensions**

CPS20G-50-CV0 2/3

Product Net Depth / 164.04 ft
Length 50 m

Container Information	
Package Level 1 Units	1 reel
Package Level 1 Width	7.08 in 180 mm
Package Level 1 Height	6.29 in 160 mm
Package Level 1 Depth / Length	7.08 in 180 mm
Package Level 2 Units	5 reel
Package Level 2 Width	14.76 in 375 mm
Package Level 2 Height	13.58 in 345 mm
Package Level 2 Depth / Length	29.53 in 750 mm

Additional Information	
Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Gray
Effective Date	20071010
Material	Polyester
Product Name	OTHER ARTICLES OF YARN
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F
	-50 to 150 °C

Certificates and Declarations		
Data Sheet, Technical Information	CPS20G-50-CV0	

Classifications		
ETIM 6	EC001937 - Cable protection for installation duct	
ETIM 7	EC001937 - Cable protection for installation duct	
ETIM 8	EC001937 - Cable protection for installation duct	
UNSPSC	39131602	
WEEE Category	Product Not in WEEE Scope	
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving	

CPS20G-50-CV0 3/3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Installation\ Products \rightarrow Wire\ Management\ and\ Connectivity \rightarrow Cable\ Ties$ 

