



PRODUCT-DETAILS

CPS3G-100-CV0
BR. SLEEVE CONF CV0 GREY



General Information	
Extended Product Type	CPS3G-100-CV0
Product ID	7TCG054800R0108
EAN	5415022238181
Catalog Description	BR. SLEEVE CONF CV0 GREY
Long Description	Flame Retardant Braided Sleeve, Gray Polyester for Temperatures -50 Degrees Celsius (-58 F) up to 150 Celsius (302 F), Nominal Diameter 3mm (0.118 Inches), Expandable Diameter Range 2mm (0.079 Inches) to 5mm (0.197 Inches), Mini-Reel Length 100m (328.08 Feet)

Ordering	
EAN	5415022238181
UPC	786209882516
Country of Origin	France (FR)
Selling Unit of Measure	roll

Dimensions	
Product Net Depth / Length	328.08 ft 100 m

Container Information	
Package Level 1 Units	1 reel
Package Level 1 Width	14.76 in 375 mm
Package Level 1 Height	2.56 in 65 mm
Package Level 1 Depth / Length	14.76 in 375 mm
Package Level 2 Units	5 reel
Package Level 2 Width	14.76 in 375 mm
Package Level 2 Height	14.57 in 370 mm
Package Level 2 Depth / Length	14.76 in 375 mm

Additional Information	
Brand / Label	Catamount
Bundle Diameter	0.04 to 2.6 in 1 to 66 mm
Color	Gray
Effective Date	20140408
Material	Polyester
Product Name	PLASTIC CONDUIT
Product Type	Braided Sleeve
Temperature Range	-58 to 302 °F -50 to 150 °C

Certificates and Declarations	
Data Sheet, Technical Information	CPS3G-100-CV0

Classifications	
ETIM 6	EC001937 - Cable protection for installation duct
ETIM 7	EC001937 - Cable protection for installation duct
ETIM 8	EC001937 - Cable protection for installation duct
UNSPSC	39131602
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5392 >> Expandable braided sleeving

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

