CSU-2MV 1/3



PRODUCT-DETAILS

CSU-2MV

CSU-2MV Current Sensing Unit



General Information	Genera	Inform	ation
---------------------	--------	--------	-------

Extended Product Type	CSU-2MV	
Product ID	1SFA664002R8001	
EAN	7320500524930	
Catalog Description	CSIL-2MV Current Sensing Unit	

Long Description

Current sensing unit CSU-2MV is an accessory to the Arc Guard System TVOC-2 when dual conditioning of light and current is needed to prevent nuisance tripping of the Arc Guard System. Designed to be used in medium voltage applications. Connect 1-4 current sensors KECA... and KEVCD... to the CSU-2MV to measure L1-L3 and Neutral. Measures wide range of nominal current 0,1... 4 kA and over current 0,1... 12 kA. The unit sends a continuous light to the TVOC-2 while no over current or error occurs. Settings for over current level, warning current level, measured phases etc. are done in the touch screen or through Modbus RTU communication protocol. K1 signal relay is a change-over contact that can be used to signal over current to other system. Combine the CSU-2MV with accessories TVOC-2-OP... to daisy chain several current sensing units and to connect ot TVOC-2 main unit. Rated supply voltage 24... 240 V AC, 24... 250 $\,$

Circular Value

Toxic Substances 2CMT001035D0902a Control Act - TSCA

CSU-2MV 2/3

Environmental	
Ambient Air	Operation -25 +70 °C
Temperature	Storage -25 +85 °C
REACH Declaration	2AGS2022-006202
RoHS Information	2AGS2022-006277-RoHS
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Ordering		
EAN		

Minimum Order Quantity1 pieceCustoms Tariff Number85389099

DimensionsProduct Net Width155.5 mmProduct Net Height141.1 mmProduct Net Depth /
Length63.8 mmProduct Net Weight0.42 kg

Package Level 1 Units box 1 piece Package Level 1 Width 203 mm Package Level 1 Height 126 mm Package Level 1 Depth / 206 mm Length Package Level 1 Gross 0.58 kg Weight

Additional Information	
Mounting Type	Wall mounted or DIN
Number of Auxiliary Contacts CO (SPDT)	1
Product Main Type	TVOC-2
Product Name	Current Sensing Unit
Rated Operational Voltage	24 240 V AC 24 250 V DC
RoHS Date	1009 1
Suitable For	TVOC-2
Terminal Type	Screw Terminals

Certificates and Declarations	
1SFC170001C0201	
1SFC170021D2701	

Package Level 1 EAN

7320500524930

7320500524930

CSU-2MV 3/3

Instructions and 1SFC170020M0201 Manuals

Classifications	
ETIM 7	EC001440 - Current monitoring relay
ETIM 8	EC001439 - Timer relay
ETIM 9	EC001439 - Timer relay
UNSPSC	39122331
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
eClass	V11.0 : 27371605

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Circuit\ Breakers \rightarrow External\ Digital\ Unit \rightarrow Arc\ Guard\ System$ $Medium\ Voltage\ Products\ and\ Systems \rightarrow Service \rightarrow Spares\ and\ Consumables \rightarrow Parts \rightarrow All\ Spare\ Parts\ (Relays-SWG-CB)$

