



PRODUCT-DETAILS

CT-SDS.22P

CT-SDS.22P Time relay, star-delta 2n/o, 24-48VDC, 24-240VAC



General Information	
Extended Product Type	CT-SDS.22P
Product ID	1SVR740210R3300
EAN	4016779851749
Catalog Description	CT-SDS.22P Time relay, star-delta 2n/o, 24-48VDC, 24-240VAC
Long Description	<p>The CT-SDS.22P is a single-function electronic time relay from the CT-S timer range. It provides a star-delta function with 7 time ranges from 0.05 s to 10 min. and a fixed transition time of 50 ms. This time relay operates with a rated control supply voltage of 24 - 48 V DC / 24 - 240 V AC and has a 2 n/o output with contacts rated at 250 V / 4 A. A sealable transparent cover for protection against unauthorized changes is available as accessory.</p> <p>The device offers maintenance free Easy Connect Technology with push-in terminals.</p>

Ordering	
EAN	4016779851749
Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical	2CDC110004C0210_01

Information

Instructions and Manuals	1SVC730050M1000 1SVC730050M0000
CAD Dimensional Drawing	2CDC001079B0201

Dimensions

Product Net Width	22.5 mm
Product Net Height	85.6 mm
Product Net Depth / Length	103.7 mm
Product Net Weight	0.108 kg

Technical

Timer Relay Type	Star-Delta
Time Range	0.05 s ... 10 min
Rated Control Supply Voltage (U_s)	24 ... 240 V AC 24 ... 48 V DC
Rated Operational Voltage	Auxiliary Circuit 250 V
Rated Frequency (f)	50 / 60 Hz DC
Output	2 n/o contacts
Terminal Type	Screwless Terminals
Rated Operational Current AC-12 (I_{θ})	(230 V) 4 A
Rated Operational Current AC-15 (I_{θ})	(230 V) 3 A
Rated Operational Current DC-12 (I_{θ})	(24 V) 4 A
Rated Operational Current DC-13 (I_{θ})	(24 V) 2 A
Minimum Switching Capacity	12 V 100 mA
Rated Impulse Withstand Voltage (U_{imp})	Input Circuit 4 kV Output Circuit 1 / Output Circuit 2 4 kV
Rated Insulation Voltage (U_i)	Input Circuit / Output Circuit 500 V Output Circuit 1 / Output Circuit 2 300 V
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Electrical Durability	AC-12 100000 cycle
Mechanical Durability	30000000 cycle
Connecting Capacity	Flexible with Ferrule 2x 0.5 ... 1.5 mm ² Flexible with Insulated Ferrule 2x 0.5 ... 1.5 mm ² Flexible 2x 0.5 ... 1.5 mm ² Rigid 2x 0.5 ... 1.5 mm ²
Wire Stripping Length	8 mm
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 61812-1 UL 508

Technical UL/CSA	
Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16 AWG Rigid 2x 20-16 AWG
Pilot Duty UL/CSA	B300
Flammability According to UL94	V-0

Environmental	
Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SVD981001-4501
RoHS Information	1SVD981008
RoHS Status	Following EU Directive 2011/65/EU

Circular Value	
End of Life Instructions	1SAC200290H0001
Environmental Information	1SAC200095H0001

Certificates and Declarations	
CQC Certificate	CQC2007010303255979
cULus Certificate	cULus508_20110711-E140448A
Declaration of Conformity - CCC	2020980303000207
Declaration of Conformity - CE	1SVD981008
Declaration of Conformity - UKCA	1SVD981008-10
DNV GL Certificate	DNV_GL_TAA00000XR
EAC Certificate	EAC_RU_C-DE.ME77.B.00568/20
RMRS Certificate	RMRS 1740021250

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	97 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Height	109 mm
Package Level 1 Gross Weight	0.13 kg
Package Level 1 EAN	4016779851749

Classifications

Object Classification Code	K
ETIM 7	EC001439 - Timer relay
ETIM 8	EC001439 - Timer relay
ETIM 9	EC001439 - Timer relay
eClass	V11.0 : 27371605
UNSPSC	39122329
E-Number (Finland)	2712230
E-Number (Sweden)	4033142

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Time Relays → CT-S

