



PRODUCT-DETAILS

DS202CR M C6 A300

DS202CR M C6 A300 Residual Current Circuit Breaker with Overcurrent Protection



General Information	
Extended Product Type	DS202CR M C6 A300
Product ID	2CSR772140R3064
EAN	4022903034643
Catalog Description	DS202CR M C6 A300 Residual Current Circuit Breaker with Overcurrent Protection
Long Description	The DS202CR series RCBO is a 2P in two-modules device for the protection of end user single-phase circuits against overload and short-circuit currents. Protection against the effects of sinusoidal alternating and direct pulsating earth fault currents. Protection against indirect contacts and additional protection against direct contacts.

Eco Transparency	
Environmental Product Declaration - EPD	9AKK108467A5738

Technical	
Standards	IEC/EN 61009-1 IEC/EN 61009-2-1

Tripping Characteristic	C
Type of Residual Current	Type A
Rated Operational Voltage	acc. to IEC 60898-1 230 V
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Input Voltage Type	AC
Rated Current (I _n)	6 A
Rated Residual Current	300 mA
Rated Short-Circuit Capacity	10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	10 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs})	7.5 kA
Maximum Surge Current	0.25 kA
Leakage Current Type	A
Frequency (f)	50 Hz
Rated Frequency (f)	50 Hz
Power Loss	3.04 W
Power Supply Connection	Arbitrary
Energy Limiting Class	3
Electrical Endurance	10000 operations
Mechanical Endurance	20000 operations
Number of Protected Poles	2
Number of Poles	2
Fault Indication	Blue flag on window
Operating Characteristic	Instantaneous
Overvoltage Category	III
Position of Neutral Terminals	Right Left
Tightening Torque	4 N·m
Accessory Type	Auxiliary contact Signal contact / auxiliary contact
Earthing Switch Type	Undelayed
Mounting Type	DIN-Rail
Mounting Position	Any
Accessories Available	Yes
Number of Batteries	0
Cable Size	35 mm ²
Connecting Capacity	Busbar 10...10 mm ² Flexible 1...25 mm ² Rigid Solid 1...35 mm ²
Rated Cross-Section	1 - Solid-Core 1 ... 35 mm ² 4 - Multi-Wired 1 ... 25 mm ²
Wire Stripping Length	11 mm

Material Compliance

RoHS Information	9AKK108466A5162
------------------	-----------------

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	20220211
REACH Declaration	9AKK108466A9708
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air Temperature	Operation -25 ... 55 °C
Degree of Protection	IP20
Pollution Degree	3
Environmental Conditions	28 cycle with 55 °C / 90-96 % and 25 °C / 95-100 %

Dimensions

Width in Number of Modular Spacings	2
Product Net Width	36 mm
Product Net Height	86 mm
Product Net Depth / Length	72 mm
Product Net Weight	0.220 kg
Built-In Depth (t ₂)	72 mm

Ordering

Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.245 kg

Certificates and Declarations

ABS Certificate	9AKK108467A7630
Declaration of Conformity - CE	9AKK108466A5162
IMQ Certificate	9AKK108467A6462
NF Certificate	9AKK108467A7737
RINA Certificate	9AKK108467A7089
VDE Certificate	9AKK108467A7823

Installation

Instructions and Manuals	9AKK108466A5165
--------------------------	-----------------

Popular Downloads

Data Sheet, Technical Information	9AKK108467A1864
-----------------------------------	-----------------

Classifications		
ETIM 8	EC000905 - Earth leakage circuit breaker	
ETIM 9	EC000905 - Earth leakage circuit breaker	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Consumer	
CN8	85363010	
eClass	V11.0 : 27142207	
Object Classification Code	F	

Accessories				
Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200931R0001	G2C-H6-L+R Signal / Auxiliary Contact	G2C-H6-L+R	1	piece
2CDS200932R0001	G2C-S/H6-L+R Signal / Auxiliary Contact	G2C-S/H6-L+R	1	piece
2CDS200932R0011	G2C-S/H6-L+R-KL Signal / Auxiliary Contact	G2C-S/H6-L+R-KL	1	piece

Categories
Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Circuit Breakers with Overcurrent Protection RCBO

