DS203NC B25 A30 1/4



PRODUCT-DETAILS

DS203NC B25 A30

DS203NC B25 A30 Residual Current Circuit Breaker with Overcurrent Protection



General Information	
Extended Product Type	DS203NC B25 A30
Product ID	2CSR256140R1255
EAN	8012542077725
Catalog Description	DS203NC B25 A30 Residual Current Circuit Breaker with Overcurrent Protection
Long Description	DS203NC is a 3P+N residual current circuit breaker with overcurrent protection (RCBO) in four modules for the protection against short-circuit currents, overload, earth fault currents, indirect contacts, additional protection against direct contacts.

Technical	
Standards	IEC 61009-1
	IEC 61009-2-1
	EN 61009-1
	EN 61009-2-1
Tripping Characteristic	В
Type of Residual Current	Type A
Rated Voltage (U _r)	400-415 V AC
Rated Operational	acc. to IEC 60898-1 415 V
Voltage	

DS203NC B25 A30 2/4

Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Input Voltage Type	AC
Rated Current (In)	25 A
Rated Residual Current	30 mA
Rated Short-Circuit Capacity	6 kA
Rated Ultimate Short- Circuit Breaking Capacity (I _{cu})	10 kA
Rated Conditional Short- Circuit Current (I _{nc})	10 kA
Rated Service Short- Circuit Breaking Capacity, in % of Icu (I _{cs})	6 kA
Leakage Current Type	A
Frequency (f)	50/60 Hz
Rated Frequency (f)	50 60 Hz
Power Loss	10.3 W
Power Supply Connection	Arbitrary
Energy Limiting Class	3
Electrical Endurance	10000 cycle
Mechanical Endurance	20000 cycle
Number of Protected Poles	3
Number of Poles	4
Operating Characteristic	Instantaneous
Overvoltage Category	III
Position of Neutral Terminals	Right
Earthing Switch Type	Undelayed
Release Type	В
Options Provided	None
Accessories Available	Yes
Connecting Capacity	Busbar 10 mm² Rigid 25 25 mm² Flexible 25 25 mm²
Rated Cross-Section	1 - Solid-Core 25 25 mm² 4 - Multi-Wired 1 25 mm²

Material Compliance	
RoHS Information	9AKK106713A5597
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20150415
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Temperature -25...55 °C

DS203NC B25 A30 3/4

Ambient Air	Operation -25 55 °C
Temperature	
Degree of Protection	IP2X
Pollution Degree	2
Environmental Information	refer to RoHS information

Dimensions	
Width in Number of Modular Spacings	4
Product Net Width	0.071 m
Product Net Height	0.085 m
Product Net Depth / Length	0.069 m
Product Net Weight	0.480 kg
Built-In Depth (t ₂)	69 mm
Dimension Diagram	9AKK106930A2210

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.530 kg
E-Number (Finland)	3211118

Certificates and Declarations	
CCC Certificate	2021980307001650
Declaration of	9AKK106713A5597
Conformity - CE	

Installation	
Instructions and	9AKK106713A8790
Manuals	

Popular Downloads	
Data Sheet, Technical	2CSC423030B0201
Information	

Classifications	
ETIM 8	EC000905 - Earth leakage circuit breaker
ETIM 9	EC000905 - Earth leakage circuit breaker
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363030
eClass	V11.0 : 27142207
Object Classification Code	F

DS203NC B25 A30 4/4

Identifier 2CDS200912R0001	Description S2C-H6R Auxiliary Contact	Type Quantity		Unit Of Measure
		S2C-H6R	1	piece
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CSS200910R0005	S2C-OVP1 Overvoltage Release	S2C-OVP1	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage Release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage Release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage ReleaseS	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200923R0001	SN201-IH Interface module with auxiliary contact	SN201-IH	1	piece
2CSS200924R0001	SN201-S Signal Contact	SN201-S	1	piece
2CSS200933R0011	F2C-A1 Shunt trip	F2C-A1	1	piece
2CSS200933R0012	F2C-A2 Shunt trip	F2C-A2	1	piece
2CSS200993R0005	S2C-OVP2 Overvoltage Release	S2C-OVP2	1	piece

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Residual\ Current\ Devices\ RCDs\ \rightarrow\ Residual\ Current\ Circuit\ Breakers\ with\ Overcurrent\ Protection\ RCBO$





