DS203NC C16 APR30 1/4



PRODUCT-DETAILS

DS203NC C16 APR30

DS203NC C16 APR30 Residual Current Circuit Breaker with Overcurrent Protection



General Information		
Extended Product Type	DS203NC C16 APR30	
Product ID	2CSR256440R1164	
EAN	8012542261421	
Catalog Description	DS203NC C16 APR30 Residual Current Circuit Breaker with Overcurrent Protection	
Long Description	DS203NC is a 3P+N residual current circuit breaker with overcurrent protection (RCBO) in four modules for the protection against short-circuit currents, overload, earth fault currents, indirect contacts, additional protection against direct contacts.	

Technical	
Standards	IEC 61009-1
	IEC 61009-2-1
	EN 61009-1
	EN 61009-2-1
Tripping Characteristic	С
Type of Residual Current	Type A
Rated Voltage (U _r)	400-415 V AC
Rated Operational	acc. to IEC 60898-1 415 V
Voltage	

DS203NC C16 APR30 2/4

Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 500 V		
Rated Impulse Withstand Voltage (U _{imp})	4 kV		
Input Voltage Type	AC		
Rated Current (In)	16 A		
Rated Residual Current	30 mA		
Rated Short-Circuit Capacity	6 kA		
Rated Ultimate Short- Circuit Breaking Capacity (I _{cu})	10 kA		
Rated Conditional Short- Circuit Current (I _{nc})	10 kA		
Rated Service Short- Circuit Breaking Capacity, in % of Icu (I _{cs})	6 kA		
Maximum Surge Current	3 kA		
Leakage Current Type	A		
Frequency (f)	50/60 Hz		
Rated Frequency (f)	50 60 Hz		
Power Loss	10 W		
Power Supply Connection	Arbitrary		
Energy Limiting Class	3		
Electrical Endurance	10000 cycle		
Mechanical Endurance	20000 cycle		
Number of Protected Poles	3		
Number of Poles	4		
Operating Characteristic	Instantaneous (APR High Immunity)		
Overvoltage Category	III		
Position of Neutral Terminals	Right		
Earthing Switch Type	Short-Time Delayed		
Release Type	С		
Options Provided	None		
Accessories Available	Yes		
Connecting Capacity	Busbar 10 mm² Rigid 25 25 mm² Flexible 25 25 mm²		
Rated Cross-Section	1 - Solid-Core 25 25 mm² 4 - Multi-Wired 1 25 mm²		

Material Compliance	
RoHS Information	9AKK106713A5597
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20150415
REACH Declaration	9AKK108467A9482
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

DS203NC C16 APR30 3/4

Ambient Temperature	-2555 °C		
Ambient Air	Operation -25 55 °C		
Temperature			
Degree of Protection	IP2		
Pollution Degree			
Environmental Information	refer to RoHS informatio		
Dimensions			
Width in Number of Modular Spacings			
Product Net Width	0.071 r		
Product Net Height	0.085 r		
Product Net Depth / Length	0.069 m		
Product Net Weight	0.480 kg		
Built-In Depth (t ₂)			
	0.480 kg 69 mn box 1 piece		
Ordering Package Level 1 Units Package Level 1 Gross	69 mn		
Built-In Depth (t ₂) Ordering Package Level 1 Units	69 mr box 1 piec		
Ordering Package Level 1 Units Package Level 1 Gross Weight E-Number (Sweden)	box 1 piec 0.530 kg		
Ordering Package Level 1 Units Package Level 1 Gross Weight	box 1 piec 0.530 kg		
Ordering Package Level 1 Units Package Level 1 Gross Weight E-Number (Sweden) Certificates and Declarations	69 mr box 1 piec 0.530 k 216007		
Ordering Package Level 1 Units Package Level 1 Gross Weight E-Number (Sweden) Certificates and Declarations CCC Certificate Declaration of	69 mr box 1 piec 0.530 k 216007		

Data Sheet, Technical Information

Popular Downloads

ETIM 8	EC000905 - Earth leakage circuit breaker
ETIM 9	EC000905 - Earth leakage circuit breaker
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85363010
eClass	V11.0 : 27142207
Object Classification Code	F

2CSC423030B0201

DS203NC C16 APR30 4/4

Identifier 2CDS200912R0001	Description	Type Quantity		Unit Of Measure
	S2C-H6R Auxiliary Contact	S2C-H6R	1	piece
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CSS200910R0005	S2C-OVP1 Overvoltage Release	S2C-OVP1	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage Release	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage Release	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage ReleaseS	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200923R0001	SN201-IH Interface module with auxiliary contact	SN201-IH	1	piece
2CSS200924R0001	SN201-S Signal Contact	SN201-S	1	piece
2CSS200933R0011	F2C-A1 Shunt trip	F2C-A1	1	piece
2CSS200933R0012	F2C-A2 Shunt trip	F2C-A2	1	piece
2CSS200993R0005	S2C-OVP2 Overvoltage Release	S2C-OVP2	1	piece

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Residual\ Current\ Devices\ RCDs\ \rightarrow\ Residual\ Current\ Circuit\ Breakers\ with\ Overcurrent\ Protection\ RCBO$





