DS203NC L C20 AC30 1/4



PRODUCT-DETAILS

DS203NC L C20 AC30 DS203NC L C20 AC30 Residual Current Circuit Breaker with Overcurrent Protection



General Information		
Extended Product Type	DS203NC L C20 AC30	
Product ID	2CSR246040R1204	
EAN	8012542343424	
Catalog Description	DS203NC L C20 AC30 Residual Current Circuit Breaker with Overcurrent Protection	
Long Description	DS203NC is a 3P+N residual current circuit breaker with overcurrent protection (RCBO) in four modules for the protection against short-circuit currents, overload, earth fault currents, indirect contacts, additional protection against direct contacts	

Technical	
Standards	IEC 61009-1 IEC 61009-2-1 EN 61009-1 EN 61009-2-1
Tripping Characteristic	С
Type of Residual Current	Type AC
Rated Voltage (U _r)	400-415 V AC
Rated Operational Voltage	acc. to IEC 60898-1 415 V
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand	4 kV

DS203NC L C20 AC30 2/4

Input Voltage Type	AC		
Rated Current (I _n)	20 A		
Rated Residual Current	30 m/		
Rated Short-Circuit	4.5 kA		
Capacity	1.010		
Rated Ultimate Short-	6 kA		
Circuit Breaking Capacity			
(l _{cu})			
Rated Conditional Short- Circuit Current (I _{nc})	6 kA		
Rated Service Short-	4.5 kA		
Circuit Breaking Capacity,	1.0 10		
in % of lcu (l _{cs})			
Maximum Surge Current	0.25 kA		
Leakage Current Type	AC		
Frequency (f)	50/60 Hz		
Rated Frequency (f)	50 60 Hz		
Power Loss	11.8 W		
Power Supply Connection	Arbitrary		
Energy Limiting Class	3		
Electrical Endurance	10000 cycle		
Mechanical Endurance	20000 cycle		
Number of Protected	3		
Poles			
Number of Poles	4		
Operating Characteristic	Instantaneous		
Overvoltage Category			
Position of Neutral Terminals	Right		
Earthing Switch Type	Undelayed		
Release Type	C		
Options Provided	None		
Accessories Available	Yes		
Connecting Capacity	Busbar 10 mm² Rigid 25 25 mm² Flexible 25 25 mm²		
Rated Cross-Section	1 - Solid-Core 25 25 mm²		
	4 - Multi-Wired 1 25 mm ²		
Material Compliance			
RoHS Information	9AKK106713A5597		
RoHS Status	Following EU Directive 2011/65/EU		
RoHS Date	20150415		
REACH Declaration	9AKK108467A9482		
Conflict Minerals	9AKK108468A3363		
Reporting Template (CMRT)			
(Similar)			
Environmental			
Ambient Temperature	-2555 °C		
Ambient Air Temperature	Operation -25 55 °C		
Degree of Protection	IP2X		
Pollution Degree	2		
nvironmental Information refer to Rol-			

DS203NC L C20 AC30 3/4

Width in Number of	4			
Modular Spacings Product Net Width	0.071 m			
Product Net Width Product Net Height	0.071 m 0.085 m			
Product Net Depth /	0.069 m			
Length	0.000			
Product Net Weight	0.480 kg			
Built-In Depth (t ₂)	69 mm			
Ordering				
Package Level 1 Units	box 1 piece			
Package Level 1 Gross Weight	0.530 kg			
Certificates and Declarations				
CCC Certificate	2021980307001650			
Declaration of Conformity - CE	9AKK106713A5597			
Installation				
Instructions and Manuals	9AKK106713A8790			
Popular Downloads				
Data Sheet, Technical Information	2CSC423030B0201			
Classifications				
ETIM 8	EC000905 - Earth leakage circuit breaker			
ETIM 9	EC000905 - Earth leakage circuit breaker			
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)			
WEEE B2C / B2B	Business To Consumer			
CN8	85363030			
eClass	V11.0 : 27142207			
Object Classification Code	<u> </u>			

Accessories

DS203NC L C20 AC30 4/4

Identifier	Description	Туре	Quantity	Unit Of Measure
2CDS200912R0001	S2C-H6R Auxiliary Contact	S2C-H6R	1	piece
2CDS200922R0001	S2C-S/H6R Signal / Auxiliary Contact	S2C-S/H6R	1	piece
2CSS200910R0005	S2C-OVP1 Overvoltage Release	S2C-OVP1	1	piece
2CSS200911R0002	S2C-UA 24 AC Undervoltage Release S	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC Undervoltage Release S	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC Undervoltage Release	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC Undervoltage Release	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC Undervoltage Release	S2C-UA 400 AC	1	piece
2CSS200923R0001	SN201-IH Interface module with auxiliary contact	SN201-IH	1	piece
2CSS200924R0001	SN201-S Signal Contact	SN201-S	1	piece
2CSS200933R0011	F2C-A1 Shunt trip	F2C-A1	1	piece
2CSS200933R0012	F2C-A2 Shunt trip	F2C-A2	1	piece
2CSS200993R0005	S2C-OVP2 Overvoltage Release	S2C-OVP2	1	piece

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Residual\ Current\ Devices\ RCDs \rightarrow Residual\ Current\ Circuit\ Breakers\ with\ Overcurrent\ Protection\ RCBO$





