

PRODUCT-DETAILS

M1173 M1173 Socket outlet



M1173
2CSM110000R0701
8012542004103
M1173 Socket outlet
This modular socket allows the connection of devices, tools or electrical and electronic non modular equipments in civil and industrial electrical switchboards.

Technical	
Rated Voltage (U _r)	250 V
Rated Current (I _n)	16 A
Power Loss	at Rated Operating Conditions per Pole 0.6 W
Model Number	Other
Number of Active Pin Terminals	0
Product Type	Italian P30 Standard
Color	Grey

M1173 2/3

Material Compliance	
RoHS Information	9AKK107492A6968
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20170426
REACH Declaration Conflict Minerals	9AKK108467A9482 9AKK108468A3363
Reporting Template (CMRT)	3AN 100400A3303
Environmental	
Degree of Protection	IP20
Environmental Information	See RoHS Information
Dimensions	
Width in Number of Modular Spacings	2.5
Product Net Width	0.045 m
Product Net Height Product Net Depth /	0.085 m 0.070 m
Length	0.070 III
Product Net Weight	0.115 kg
Built-In Depth (t ₂)	60 mm
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.54 kg
E-Number (Finland)	2519720
E-Number (Sweden)	2102800
Certificates and Declarations	
Declaration of Conformity - CE	9AKK107492A6968
Installation	
Instructions and Manuals	No document needed
Popular Downloads	
Data Sheet, Technical	2CSC400002D0209
Information	
Classifications	
ETIM 8	EC001663 - Socket outlet for distribution board
ETIM 9	EC001663 - Socket outlet for distribution board
WEEE R2C / R2R	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

M1173 3/3

 CN8
 85369010

 eClass
 V11.0:27142305

 Object Classification Code
 X

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Command\ and\ Signalling\ Devices \rightarrow Socket\ Outlets$





