



PRODUCT-DETAILS

US/U12.2

US/U12.2 Universal Interface, 12-fold, FM



General Information	
Extended Product Type	US/U12.2
Product ID	2CDG110065R0011
EAN	4016779650120
Catalog Description	US/U12.2 Universal Interface, 12-fold, FM
Long Description	The Universal Interface has 12 channels which can be parameterised as inputs or outputs, e.g. for connection of conventional push-buttons or LEDs. The LEDs are supplied by the device (1.5 mA), the series resistances are integrated.
Installation	
Instructions and Manuals	2CDG941021P0002
Mounting Type	Flush Mounted
Technical	
Data Sheet, Technical Information	2CDC504056D0201
Sub-Function	LED controlling
Number of Outputs	12

Maximum Number of Switching Outputs	12
Number of Inputs	Analog (0 ... 10 V / 4 ... 20 mA) 12
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Manual Operation	No
Number of Batteries	0

Electrical

Current Type	DC
Input Voltage Type	pulsed
Power Loss	0.25 W

Design

Color	white
-------	-------

Material Compliance

RoHS Information	2CDK510080D2701
RoHS Status	Following EU Directive 2011/65/EU
REACH Declaration	9AKK108468A9644
REACH Information	False - does not contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
SCIP	3bc27e15-09a4-4851-8d8e-eaf639019c0e Germany (DE)

Environmental

Degree of Protection	IP20
----------------------	------

Dimensions

Product Net Width	54 mm
Product Net Height	19 mm
Product Net Depth / Length	54 mm
Product Net Weight	0.068 kg

Certificates and Declarations

CB Certificate	9AKK107991A3201
Declaration of Conformity - CE	2CDK510080D2701
KNX Certificate	9AKK105710A0120

Classifications

ETIM 9	EC001584 - I/O device for bus system
eClass	V11.0 : 27143145
UNSPSC	39122221
Object Classification Code	A

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

Categories

Low Voltage Products and Systems → Building and Home Automation Solutions → KNX → Standard Inputs → Universal Interfaces

