6190/45 1/3



PRODUCT-DETAILS

6190/45

6190/45 Brightness Sensor, SM



General Information	
Extended Product Type	6190/45
Product ID	2CKA006190A0035
EAN	4011395988527
Catalog Description	6190/45 Brightness Sensor,SM
	For Weather Station 6190/40-101. Serves for converting the measured light value
Long Description	(3,000-60,000 lux) into electrical signals (0-10 V). Surface mounting box IP 65 Recommended supply lead 3 x 0.25 mm² (max. 100 m)

Installation		
Instructions and Manuals	2CKA000173B6194	
Wiring Diagram	2CKA000097E0065	
Mounting Type	Surface Mounted	

Technical	
Compatible Bus Systems	KNX (TP)

2/3 6190/45

Product Range	KNX
Number of Batteries	(
Electrical	
Rated Voltage (U _r)	24\
Auxiliary Voltage AC/DC	24 V AC/D0
Material Compliance	
RoHS Information	2CKA200000E4758
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 201
REACH Declaration	2CKA309999E9999
REACH Information	False - does not contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Environmental Ambient Air	Operation -30 +70 °C
Temperature	
Degree of Protection	IP65
Dimensions	
Product Net Width	58 mn
Product Net Height	92.5 mn
Product Net Depth / Length	35 mn
Product Net Weight	89 (
Dimension Diagram	2CKA000097E064
Certificates and Declarations	
Declaration of Conformity - CE	2CKA100000E1299
Classifications	
ETIM 9	EC000533 - Lighting control system componen
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm
WEEE B2C / B2B	Business To Consume

6190/45 3/3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow Standard\ Inputs \rightarrow Metrological\ and\ Physical\ Sensors$

