

PRODUCT-DETAILS

SD/S 2.16.1 SD/S2.16.1 Switch-/Dim Actuator, 2-fold, 16 A, MDRC



| Extended Product Type | SD/S 2.16.1 |
|--|---|
| Product ID | 2CDG110079R0011 |
| EAN | 4016779659963 |
| Catalog Description | SD/S2.16.1 Switch-/Dim Actuator, 2-fold, 16 A, MDRC |
| Long Description | MDRC Devices for switching and dimming of 2, 4 or 8 independent groups of luminaries with electrical ballasts and 1-10V control inputs. Per channel a potential free relay can be switched on or off via the ABB i-bus® or manually. Manual and visual operation is included. A power supply is not necessary. |
| | |
| Installation | |
| Installation Instructions and Manuals | 2CDG941042P0003 |
| Instructions and | 2CDG941042P0003 DIN-Rail |
| Instructions and Manuals | |
| Instructions and Manuals Mounting Type | |

Subject to change without notice

SD/S 2.16.1

| Information | 2CDC507071D0201 |
|------------------------|-----------------|
| Number of Outputs | 2 |
| Compatible Bus Systems | KNX (TP) |
| Product Range | KNX |
| Manual Operation | Yes |
| Number of Batteries | 0 |

Electrical

| Rated Operational | 110 230 V AC |
|------------------------------------|--------------|
| Voltage | |
| Auxiliary Voltage AC/DC | KNX |
| Output Voltage (U _{out}) | 230 V AC |
| Maximum Switching | 16 A |
| Current | |
| Maximum Control | 100 mA |
| Current DC | |
| Rated Frequency (f) | 50 / 60 Hz |
| Load Type | Universal |
| Power Loss | 2.6 W |

Design

| Material Compliance | |
|---|--|
| RoHS Information | 2CDK507125D2701 |
| RoHS Status | Following EU Directive 2011/65/EU |
| REACH Declaration | 9AKK108468A9644 |
| REACH Information | False - does not contains substances > 0.1 mass percentage |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

| Environmental | |
|----------------------|------|
| Degree of Protection | IP20 |

| Dimensions | |
|--|-----------------|
| Width in Number of Modular Spacings | 4 |
| Product Net Width | 72 mm |
| Product Net Height | 90 mm |
| Product Net Depth / Length | 64.5 mm |
| Product Net Weight | 0.18 kg |
| Built-In Depth (t ₂) | 64.5 mm |
| Dimension Diagram | 2CDC072033F0015 |

© 2024 ABB. All rights reserved.

light grey

Certificates and Declarations

Declaration of Conformity - CE KNX Certificate 2CDK507125D2701

9AKK105710A0104

| Classifications | |
|-------------------------------|--|
| ETIM 9 | EC001094 - Dimming actuator for bus system |
| eClass | V11.0 : 27143123 |
| UNSPSC | 39121801 |
| Object Classification Code | A |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |

Categories

Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow Lighting Control \rightarrow 1-10V Switch / Dim Actuators and Light Controllers





