



PRODUCT-DETAILS

OT25FT4N2

OT25FT4N2 SWITCH-DISCONNECTOR



General Information	
Extended Product Type	OT25FT4N2
Product ID	1SCA104900R1001
EAN	6417019390437
Catalog Description	OT25FT4N2 SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, door mounted switch-diconnector / non-fusible diconnect switch with protected clamp terminals, handle is not included

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Environmental Information	1SCC301262D0201
Environmental Product Declaration - EPD	1SCC301278D0201
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

Eco Transparency	
Environmental Product Declaration - EPD	1SCC301278D0201

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301056M0006
Mechanical Drawings	1SCC301440F0001 1SCC301439F0001 OT16-40FT4N2.igs
Environmental Product Declaration - EPD	1SCC301278D0201

Dimensions	
Product Net Width	48.5 mm
Product Net Height	54 mm
Product Net Depth / Length	52 mm
Product Net Weight	0.13 kg

Technical	
Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 25 A (500 V) 25 A (690 V) 25 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 25 A (500 V) 25 A (690 V) 25 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 20 A (500 V) 20 A (690 V) 11 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 4 kW (400 ... 415 V) 9 kW (500 V) 9 kW (690 V) 9 kW
Conventional Free-air Thermal Current (I_{th})	$\Theta = 40\text{ }^{\circ}\text{C}$ 32 A
Conventional Thermal Current (I_{the})	Fully Enclosed 32 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 750 V
Rated Operational Voltage	Main Circuit 750 V
Rated Short-Circuit Making Capacity (I_{cm})	(690 V) 0.71 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 0.5 kA
Rated Conditional Short-Circuit Current (I_{nc})	(40 A fuse, $\leq 415\text{ V}$) 50 kA (25 A fuse, 690 V) 50 kA

Power Loss	at Rated Operating Conditions per Pole 0.6 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3 / UL 508 / CSA C22.2 No. 14
Special Functions	No
Mounting Type	Door mounting
Number of Poles	4
Cable Cross-Section	Cu 0.75 ... 10 mm²
Degree of Protection	Front IP20
Terminal Type	Screw Terminals
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Mechanical Durability	20000
Lock Type	No

Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V
Ampere Rating	30 A
Horsepower Rating UL/CSA	(110 ... 120 V AC) Single Phase 1.5 Hp (240 V AC) Single Phase 3 Hp (440 ... 480 V AC) Single Phase 7.5 Hp (550 ... 600 V AC) Single Phase 10 Hp (220 ... 240 V AC) Three Phase 7,5 Hp (440 ... 480 V AC) Three Phase 15 Hp (550 ... 600 V AC) Three Phase 20 Hp
Tightening Torque	acc. IEC 60947-1 0.8 N·m
Tightening Torque UL/CSA	7 in·lb

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	1SCC301262D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

Certificates and Declarations

ATEX Certificate	No certification needed
Declaration of Conformity - CE	1SCC301166D2703
REACH Declaration	1SCC011021D0201
UL Certificate	cULus certificate OT16-80
VDE Certificate	No certification needed

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	67 mm
Package Level 1 Depth /	79 mm

Length	
Package Level 1 Height	61 mm
Package Level 1 Gross Weight	0.14 kg
Package Level 1 EAN	6417019390437

Classifications

Object Classification Code	Q
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601436
E-Number (Sweden)	3171083

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

