



PRODUCT-DETAILS**OT2000E22****OT2000E22 SWITCH-DISCONNECTOR**

General Information

Extended Product Type	OT2000E22
Product ID	1SCA109356R1001
EAN	6417019424736
Catalog Description	OT2000E22 SWITCH-DISCONNECTOR
Long Description	4-pole, front operated, base mounted switch-diconnector, handle and shaft are not included, terminal bolt kit included

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
End of Life Instructions	1SCC301121M0201
Environmental Information	1SCC301268D0201
Environmental Product Declaration - EPD	1SCC301304D0201
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

Toxic Substances
Control Act - TSCA

1SCC011025D0201

Eco Transparency

Environmental Product
Declaration - EPD

1SCC301304D0201

Ordering

Minimum Order Quantity
Customs Tariff Number
Country of Origin

1 piece
85365080
Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC301020C0201
Instructions and Manuals	1SCC301078M0205
Mechanical Drawings	1SCC301526F0001 1SCC301525F0001 OT2500E22.igs
Environmental Product Declaration - EPD	1SCC301304D0201
End of Life Instructions	1SCC301121M0201

Dimensions

Product Net Width	598.5 mm
Product Net Height	376.5 mm
Product Net Depth / Length	145.5 mm
Product Net Weight	32.4 kg

Technical

Rated Operational Current AC-21B (I _e)	(380 ... 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A
Rated Operational Current AC-22B (I _e)	(380 ... 415 V) 2000 A (500 V) 2000 A (690 V) 2000 A
Conventional Free-air Thermal Current (I _{th})	Θ = 40 °C 2000 A
Rated Impulse Withstand Voltage (U _{imp})	12 kV
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity (I _{cm})	(690 V) 176 kA
Rated Short-time Withstand Current Low	for 1 s 55 kA

Voltage (I _{cw})	
Power Loss	at Rated Operating Conditions per Pole 55 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - Simultaneous Function
Switches Operating Mechanism	Mechanism Between the Poles 22 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Special Functions	No
Mounting Type	Base mounting
Number of Poles	4
Degree of Protection	Front IP00
Terminal Type	Lug terminals
Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
Mechanical Durability	6000
Lock Type	No

Technical UL/CSA

Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
-------------------	--------------------------------

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	ISCC301268D0201
Toxic Substances Control Act - TSCA	ISCC011025D0201

Certificates and Declarations

Declaration of Conformity - CE	ISCC301176D2702
DNV GL Certificate	ISCC301184D0203
REACH Declaration	ISCC011021D0201

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	407 mm
Package Level 1 Depth / Length	619 mm
Package Level 1 Height	190 mm
Package Level 1 Gross Weight	34.3 kg
Package Level 1 EAN	6417019424736

Classifications

Object Classification	Q
Code	
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
ETIM 9	EC000216 - Switch disconnector (low voltage)
eClass	V11.1 : 27371403
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

