



PRODUCT-DETAILS

OS50GF22N1
OS50GF22N1 SWITCH FUSE



General Information	
Extended Product Type	OS50GF22N1
Product ID	1SCA115564R1001
EAN	6417019478845
Catalog Description	OS50GF22N1 SWITCH FUSE
Long Description	Switch Fuses,Front Operated,4-pole,22 (Between the Poles),NFC,14x51,Handle and shaft not included,Switched - With Solid Link

Circular Value	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Environmental Product Declaration - EPD	1SCC311195D0201
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201
Toxic Substances Control Act - TSCA	1SCC011025D0201

Eco Transparency	
Environmental Product Declaration - EPD	1SCC311195D0201

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads	
Data Sheet, Technical Information	1SCC311013C0201
Instructions and Manuals	1SCC311036M0212
Environmental Product Declaration - EPD	1SCC311195D0201

Dimensions	
Product Net Width	136 mm
Product Net Height	112 mm
Product Net Depth / Length	109 mm
Product Net Weight	1.6 kg

Technical	
Rated Operational Current AC-21A (I_e)	(500 V) 50 A (690 V) 50 A
Rated Operational Current AC-22A (I_e)	(500 V) 50 A (690 V) 50 A
Rated Operational Current AC-23A (I_e)	(500 V) 50 A (690 V) 50 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 11 kW (400 V) 22 kW (415 V) 22 kW (500 V) 30 kW (690 V) 37 kW
Conventional Free-air Thermal Current (I_{th})	$\Theta = 40\text{ °C}$ 50 A
Conventional Thermal Current (I_{the})	Fully Enclosed 50 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	Main Circuit 690 V AC
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 2.5 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 7.5 W
Pollution Degree	3
Handle Type	Handle and shaft not included
Fourth Pole Position	Left Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating	22 (Between the Poles)

Mechanism	
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	14x51
Fuse System	NFC
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Cable Cross-Section	2.5 ... 25 mm²
Terminal Type	Screw Terminals
Tightening Torque	3 N·m 4 N·m
Rated Current (I _n)	Main Circuit 50 A

Technical UL/CSA

Tightening Torque	3 N·m 4 N·m
-------------------	----------------

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	1SCC011025D0201

Certificates and Declarations

CCC Certificate	CCC OS32-63G_ 2016.pdf
Declaration of Conformity - CE	1SCC311136D2703
DNV GL Certificate	1SCC311125D0203
REACH Declaration	1SCC011021D0201

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	170 mm 6.7 in
Package Level 1 Depth / Length	190 mm 7.5 in
Package Level 1 Height	145 mm 5.7 in
Package Level 1 Gross Weight	1.6 kg 3.5 lb
Package Level 1 EAN	6417019478845

Classifications

Object Classification Code	Q
ETIM 7	EC001040 - Fuse switch disconnecter
ETIM 8	EC001040 - Fuse switch disconnecter
ETIM 9	EC001040 - Fuse switch disconnecter
eClass	V11.1 : 27371401
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

