CT12/1200 1/3



PRODUCT-DETAILS

CT12/1200 CT12/1200 Current transformer



General Information	
Extended Product Type	CT12/1200
Product ID	2CSG721200R1101
EAN	8012542608103
Catalog Description	CT12/1200 Current transformer
Long Description	CT12/1200 is used to transform primary currents to/5A secondary currents for c.a. measurement instruments

Technical	
Cable Use	Cable and Horizontal bar
Current Rating	1200 A
Rated Primary Current (I pn)	1200 A
Rated Secondary Current (I_{sn})	5 A
Current Limit Function	FS 5
Frequency (f)	50 60 Hz
Power Loss	40 W
Secondary Output Connection	Plug-in connection

CT12/1200 2/3

Accuracy	±0,5%
Model Number	Through-feed current converter
Number of Inputs	Primary 1
Mounting Type	Through Primary
Cable Cross-Section	2 x 50 mm
Rated Cross-Section	125 x 50 mm
Material Compliance	
RoHS Information	2CSC445004K0201
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
RoHS Date	31/03/2006 0.00.00
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
(CWITT)	
Environmental	
Ambient Air Temperature	Operation -5 50 °C
Degree of Protection	IP30
Environmental Information	See RoHS Information
Dimensions	
Product Net Width	180 mm
Product Net Height	0.196 m
Product Net Depth / Length	68.5 mm
Product Net Weight	0.680 kg
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	1.6 kg
Certificates and Declarations	
Declaration of Conformity - CE	9AKK106713A5700
Installation	
Instructions and Manuals	No document needed
Popular Downloads	
Data Sheet, Technical Information	9AKK107046A0430
Classifications	
ETIM 8	EC002048 - Current transformer

CT12/1200 3/3

ETIM 9	EC002048 - Current transformer
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer
CN8	85043121
eClass	V11.0 : 27210902
Object Classification Code	T

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Energy\ Efficiency\ Devices \rightarrow Current\ Transformers$

