



PRODUCT-DETAILS

# CEL18-10

## CEL18-10 Auxiliary Contact Block



| General Information   |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | CEL18-10                                                                                                                  |
| Product ID            | 1SFN010716R1010                                                                                                           |
| EAN                   | 7320500258590                                                                                                             |
| Catalog Description   | CEL18-10 Auxiliary Contact Block                                                                                          |
| Long Description      | 1 pole screw type side mounted low energy auxilliary contact block, instantaneous N.O. contact, suitable for use with PLC |

| Ordering               |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85369010 |

| Popular Downloads                 |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100122C0202 |
| Instructions and Manuals          | 1SFC101009M5501 |
| CAD Dimensional Drawing           | 2CDC001079B0201 |

|                            |         |
|----------------------------|---------|
| <b>Dimensions</b>          |         |
| Product Net Width          | 65 mm   |
| Product Net Depth / Length | 12 mm   |
| Product Net Height         | 74 mm   |
| Product Net Weight         | 0.04 kg |

|                                       |                                                                                                                                                                                                                                                                                                             |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Technical</b>                      |                                                                                                                                                                                                                                                                                                             |
| Number of Auxiliary Contacts NO       | 1                                                                                                                                                                                                                                                                                                           |
| Number of Auxiliary Contacts NC       | 0                                                                                                                                                                                                                                                                                                           |
| Rated Operational Voltage             | Auxiliary Circuit 125 V                                                                                                                                                                                                                                                                                     |
| Connecting Capacity Auxiliary Circuit | Flexible with Ferrule 1x 0.75 ... 2.5 mm²<br>Flexible with Ferrule 2x 0.75 ... 2.5 mm²<br>Rigid 1 x 1 ... 4 mm²<br>Rigid 2 x 1 ... 4 mm²                                                                                                                                                                    |
| Wire Stripping Length                 | Auxiliary Circuit 9 mm                                                                                                                                                                                                                                                                                      |
| Degree of Protection                  | IP20                                                                                                                                                                                                                                                                                                        |
| Terminal Type                         | Screw Terminals                                                                                                                                                                                                                                                                                             |
| Suitable For                          | AF400<br>AF460<br>AF580<br>AF750<br>AF1250<br>AF1350<br>AF1650<br>AF2050<br>AF2650<br>AF2850<br>GAF185<br>GAF300<br>GAF460<br>GAF750<br>GAF1250<br>GAF1650<br>GAF2050<br>A95<br>A110<br>A145<br>A185<br>A210<br>A260<br>A300<br>UA95<br>UA110<br>AF95<br>AF110<br>AF145<br>AF185<br>AF210<br>AF260<br>AF300 |

|                                             |                                                            |
|---------------------------------------------|------------------------------------------------------------|
| <b>Material Compliance</b>                  |                                                            |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                            |
| REACH Declaration                           | 2CMT2021-006202                                            |
| RoHS Information                            | 2CMT2021-006277                                            |
| RoHS Status                                 | Following EU Directive 2011/65/EU                          |
| WEEE B2C / B2B                              | Business To Business                                       |
| WEEE Category                               | 5. Small Equipment (No External Dimension More Than 50 cm) |

|                                      |                     |
|--------------------------------------|---------------------|
| <b>Certificates and Declarations</b> |                     |
| CQC Certificate                      | CQC2016010304912317 |
| cUL Certificate                      | 20120925-E36588     |
| Declaration of Conformity<br>- CCC   | 2020980304001268    |
| Declaration of Conformity<br>- CE    | 2CMT2015-005448     |
| Declaration of Conformity<br>- UKCA  | 2CMT2020-006119     |

|                                   |               |
|-----------------------------------|---------------|
| <b>Container Information</b>      |               |
| Package Level 1 Units             | bag 1 piece   |
| Package Level 1 Width             | 65 mm         |
| Package Level 1 Depth /<br>Length | 75 mm         |
| Package Level 1 Height            | 16.7 mm       |
| Package Level 1 Gross<br>Weight   | 0.05 kg       |
| Package Level 1 EAN               | 7320500258590 |

|                                       |                                    |
|---------------------------------------|------------------------------------|
| <b>Classifications</b>                |                                    |
| Object Classification Code            | K                                  |
| ETIM 4                                | EC000041 - Auxiliary contact block |
| ETIM 5                                | EC000041 - Auxiliary contact block |
| ETIM 6                                | EC000041 - Auxiliary contact block |
| ETIM 7                                | EC000041 - Auxiliary contact block |
| ETIM 8                                | EC000041 - Auxiliary contact block |
| eClass                                | V11.1 : 27371302                   |
| UNSPSC                                | 39121522                           |
| IDEA Granular Category<br>Code (IGCC) | 4743 >> Auxiliary contact block    |

|                                                                                     |  |
|-------------------------------------------------------------------------------------|--|
| <b>Categories</b>                                                                   |  |
| Low Voltage Products and Systems → Control Products → Contactors → Block Contactors |  |

