

PRODUCT-DETAILS

## ELR72V24P ELR72V24P Residual Current Monitor



| General Information   |  |
|-----------------------|--|
| Extended Product Type | ELR72V24P  |
| Product ID            | 2CSG452424R1202  |
| EAN                   | 8012542733829  |
| Catalog Description   | ELR72V24P Residual Current Monitor   |
| Long Description      | The ELR electronic residual current relay allows monitoring and protection of the low voltage distribution network, through the use of a toroidal transformer. Protection is achieved in combination with the MCBs and MCCBs. The ELR front panel residual current relay is compliant with protection standard 60947-2 Annex M in order to offer a cumulative operational time (residual current relay, shunt-trip, circuit breaker) quaranteed by the manufacturer. |

| Technical                            |  |
|--------------------------------------|--|
| Standards                            | IEC EN 60947-2 Ann M                               |
| Type of Residual Current             | Type A   |
| Function                             | For mixed system                                   |
| Rated Voltage (U <sub>r</sub> )      | 2448 V   |
| Rated Operational Voltage            | 24 48 V AC/DC                                      |
| Rated Control Supply Voltage $(U_s)$ | (50 Hz) 2448 V<br>(50 Hz) 2448 V<br>(60 Hz) 2448 V |

ELR72V24P 2/3

|  | (60 Hz) 2448 V<br>(DC) 2448 V   |
|--|---|
| Current Rating   | (DC) 2448 V  Response value amperage 1 30 30 mA Response value amperage 2 30000 30000 mA  |
| Rated Frequency (f)  | 50 60 Hz  |
| Power Loss   | at Rated Operating Conditions per Pole 4 W  |
| Number of Contacts   | 2   |
| Number of Contacts CO  | 2   |
| Number of Contacts NC  | 0   |
| Number of Contacts NO  | 0   |
| Delay Time (T)   | Delay-On Energization, Maximum, Permitted 5 second [unit of time]<br>Delay-On Energization, Minimum, Adjustable 0 second [unit of time] |
| Mounting Type  | Front Panel   |
| Filter Option  | no frequency filter   |
| Options Provided   | Pre-alarm threshold: 60%  |
| Material Compliance  |   |
| RoHS Information   | 9AKK106713A5721   |
| RoHS Status  | Following EU Directive 2011/65/EU   |
| RoHS Date  | 20200527  |
| Conflict Minerals Reporting Template (CMRT)  | 9AKK108468A3363   |
| Discouries and the second seco |   |
| Dimensions   |   |
| Product Net Width  | 72 mm   |
| Product Net Height Product Net Depth /   | 0.072 m<br>88 mm  |
| Length Product Net Weight  | 0.345 kg  |
| Ordering   |   |
| Package Level 1 Units  | box 1 piece   |
| Package Level 1 Gross Weight   | 0.45 kg   |
|  |   |
| Certificates and Declarations  |   |
| Declaration of Conformity - CE   | 9AKK106713A5721   |
|  |   |
| Installation   |   |
| Instructions and Manuals   | 2CSG444008D5101   |
| Popular Downloads  |   |
| Data Sheet, Technical<br>Information   | 9AKK107046A0424   |

ELR72V24P 3/3

| Classifications            |  |
|----------------------------|--|
| ETIM 8                     | EC001445 - Residual current monitoring relay               |
| ETIM 9                     | EC001445 - Residual current monitoring relay               |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B             | Business To Business                                       |
| CN8                        | 85363030   |
| eClass                     | V11.0 : 27371809   |
| Object Classification Code | E.   |

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Residual\ Current\ Devices\ RCDs \rightarrow Residual\ Current\ Monitors,\ RCMs$ 

