1/3 ELR96P



PRODUCT-DETAILS

ELR96P **ELR96P Residual Current Monitor**



General Information	
Extended Product Type	ELR96P
Product ID	2CSG152434R1202
EAN	8012542734529
Catalog Description	ELR96P Residual Current Monitor
Long Description	The ELR electronic residual current relay allows monitoring and protection of the low voltage distribution network, through the use of a toroidal transformer. Protection is achieved in combination with the MCBs and MCCBs. The ELR front panel residual current relay is compliant with protection standard 60947-2 Annex M in order to offer a cumulative operational time (residual current relay, shunt-trip, circuit breaker) quaranteed by the manufacturer.

Technical	
Standards	IEC EN 60947-2 Ann M
Type of Residual Current	Type A
Function	For AC-current system
Rated Voltage (U _r)	110400 V
Rated Operational Voltage	115-230-400 V AC
Rated Control Supply Voltage (U_s)	(50 Hz) 110400 V (60 Hz) 110400 V
Current Rating	Response value amperage 1 30 30 mA

ELR96P 2/3

	Response value amperage 2 30000 30000 mA
Rated Frequency (f)	50 60 Hz
Power Loss	at Rated Operating Conditions per Pole 4 W
Number of Contacts	2
Number of Contacts CO	2
Number of Contacts NC	0
Number of Contacts NO	Delev On Energiaction Maximum Descripted Engaged (unit of time)
Delay Time (T)	Delay-On Energization, Maximum, Permitted 5 second [unit of time] Delay-On Energization, Minimum, Adjustable 0 second [unit of time]
Mounting Type	Front Panel
Filter Option Options Provided	no frequency filter Pre-alarm threshold: 60%
Options Provided	rie-alaini uiresiioiu. 00 /a
Material Compliance	
RoHS Information	9AKK106713A5721
RoHS Status	Following EU Directive 2011/65/EU
RoHS Date	20200527
Conflict Minerals	9AKK108468A3363
Reporting Template (CMRT)	
Dimensions	
Product Net Width	96 mm
Product Net Height	96 mm
Product Net Depth /	78 mm
Length	
Product Net Weight	0.386 kg
Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.45 kg
Certificates and Declarations	
Declaration of Conformity - CE	9AKK106713A5721
Installation	
Instructions and Manuals	2CSG444010D5101
Popular Downloads	
Data Sheet, Technical	9AKK107046A0424
Information	5/11((15/045/10424
Classifications	
ETIM 8	ECONIANE Decidual convent manifestary and the
ETIM 8 ETIM 9	EC001445 - Residual current monitoring relay
WEEE Category	EC001445 - Residual current monitoring relay 5. Small Equipment (No External Dimension More Than 50 cm)
© 2024 ABB. All rights reserved.	2024/04/12 Subject to change

ELR96P 3/3

 WEEE B2C / B2B
 Business To Business

 CN8
 85363030

 eClass
 V11.0 : 27371809

 Object Classification Code
 F

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Residual\ Current\ Devices\ RCDs\ \rightarrow\ Residual\ Current\ Monitors,\ RCMs$









3605