



PRODUCT-DETAILS

CC5-01

CC5-01 Auxiliary Contact Block



General Information	
Extended Product Type	CC5-01
Product ID	1SBN010011R1001
EAN	3471522121035
Catalog Description	CC5-01 Auxiliary Contact Block
Long Description	CC5-01 is a 1-pole front mounted auxiliary contact block equipped with screw terminals and can be fitted on A9...110 serie contactors and N serie contactor relays. CC5-01 is available with one N.C. lagging contact for standard industrial environments.

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	85389099

Popular Downloads	
Data Sheet, Technical Information	1SBC100122C0202_Ch04
Instructions and	1SBC101012M5501

Manuals

CAD Dimensional Drawing	2CDC001079B0201
-------------------------	-----------------

Dimensions

Product Net Width	11 mm
Product Net Depth / Length	32.5 mm
Product Net Height	47 mm
Product Net Weight	0.014 kg

Technical

Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Auxiliary Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (380 / 400 V) 3 A
Short-Circuit Protective Devices	Auxiliary Circuit - gG Type Fuses 10 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Maximum Electrical Switching Frequency	1200 cycles per hour
Rated Operational Current DC-13 (I _e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.30 A / 66 W (250 V) 0.3 / 75 W
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V
Mechanical Durability	10 million 3 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Terminal Type	Screw Terminals
Suitable For	AF45 AF50 AF63 AF75 A9 A12 A16 A26 A30 A40 A45 A50 A63 A75

A95
A110
AL9
AL9Z
AL12
AL12Z
AL16
AL16Z
AL26
AL30
AL40
AE45
AE50
AE63
AE75
TAL9
TAL12
TAL16
TAL26
TAL30
TAL40
TAE45
TAE50
TAE75
GA75
GAE75
UA16
UA26
UA30
UA50
UA63
UA75
UA95
UA110
UA16RA
UA26RA
UA30RA
UA50RA
UA63RA
UA75RA
UA95RA
UA110RA
UAF75RA
UAF95RA
UAF110RA
N22E
N31E
N40E
NL22E
NL22ZE
NL31E
NL31ZE
NL40E
NL40ZE
TNL22E
TNL31E
TNL40E

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
Declaration of Conformity - CE	1SBD250809U1000
Declaration of Conformity - UKCA	1SBD250826U1000
EAC Certificate	EAC_RU C-FR ME77 B03391
GOST Certificate	GOST_POCCFRME77B07175
RINA Certificate	RINA_ELE172319XG001
UL Certificate	UL_071301E48139

Container Information	
Package Level 1 Units	box 10 piece
Package Level 1 Width	65 mm
Package Level 1 Depth / Length	129.5 mm
Package Level 1 Height	40 mm
Package Level 1 Gross Weight	0.14 kg
Package Level 1 EAN	3471522121035
Package Level 2 Units	box 270 piece
Package Level 2 Width	300 mm
Package Level 2 Depth / Length	245 mm
Package Level 2 Height	308 mm
Package Level 2 Gross Weight	3.78 kg
Package Level 3 Units	9720 piece

Classifications	
Object Classification Code	K
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC002498 - Accessories for low-voltage switch technology
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
ETIM 8	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39120000
E-Number (Finland)	3709236

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

