



PRODUCT-DETAILS

AF750-30-11-69

AF750-30-11 48-130V 50/60Hz / 48-130V DC

Contactors



General Information

Extended Product Type	AF750-30-11-69
Product ID	1SFL637001R6911
EAN	7320500220405
Catalog Description	AF750-30-11 48-130V 50/60Hz / 48-130V DC Contactor

Long Description	The AF750-30-11-69 is a 3 pole - 1000 V IEC or 600 V UL contactor with pre-mounted auxiliary contacts and Main Circuit Bars, controlling motors up to 400 kW / 400 V AC (AC-3) or 600 hp / 480 V UL and switching power circuits up to 1050 A (AC-1) or 900 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (48-130 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.
------------------	---

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC100192C0206
Instructions and Manuals	1SFC380023-en
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	53540919-60

Dimensions

Product Net Width	210 mm
Product Net Depth / Length	242 mm
Product Net Height	283 mm
Product Net Weight	13.6 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ }^{\circ}\text{C}$ 1050 A
Rated Operational Current AC-1 (I _e)	(1000 V) 40 °C 1000 A (1000 V) 55 °C 875 A (1000 V) 70 °C 720 A (690 V) 40 °C 1050 A (690 V) 55 °C 875 A (690 V) 70 °C 720 A
Rated Operational Current AC-3 (I _e)	(415 V) 55 °C 750 A (440 V) 55 °C 750 A (500 V) 55 °C 750 A (690 V) 55 °C 650 A (1000 V) 55 °C 300 A (380 / 400 V) 55 °C 750 A (220 / 230 / 240 V) 55 °C 750 A
Rated Operational Power AC-3 (P _e)	(415 V) 425 kW (440 V) 450 kW (500 V) 520 kW (690 V) 600 kW (1000 V) 400 kW (380 / 400 V) 400 kW (220 / 230 / 240 V) 220 kW
Rated Breaking Capacity AC-3	8 x I _e AC-3
Rated Making Capacity AC-3	10 x I _e AC-3
Short-Circuit Protective Devices	gG Type Fuses 1000 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 6400 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 1300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 3500 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 7000 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 4500 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 7500 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 7000 A
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 60 cycles per hour (AC-3) 300 cycles per hour
Rated Operational Current DC-1 (I _e)	(110 V) 1-Pole, 40 °C 1050 A (110 V) 2 Poles in Series, 40 °C 1050 A

	(220 V) 3 Poles in Series, 40 °C 1050 A (600 V) 3 Poles in Series, 40 °C 1050 A (850 V) 3 Poles in Series, 40 °C 1050 A
Rated Operational Current DC-3 (I_e)	(110 V) 1-Pole, 40 °C 1050 A (110 V) 2 Poles in Series, 40 °C 1050 A (220 V) 3 Poles in Series, 40 °C 1050 A (600 V) 3 Poles in Series, 40 °C 1050 A (850 V) 3 Poles in Series, 40 °C 1050 A
Rated Operational Current DC-5 (I_e)	(110 V) 1-Pole, 40 °C 1050 A (110 V) 2 Poles in Series, 40 °C 1050 A (220 V) 3 Poles in Series, 40 °C 1050 A (600 V) 3 Poles in Series, 40 °C 1050 A (850 V) 3 Poles in Series, 40 °C 1050 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	3 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c)	50 Hz 48 ... 130 V 60 Hz 48 ... 130 V DC Operation 48 ... 130 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage DC 5 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 1100 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 1100 V·A Pull-in at Max. Rated Control Circuit Voltage DC 1020 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 50 ... 70 ms Between Coil De-energization and NO Contact Opening 53 ... 73 ms Between Coil Energization and NC Contact Opening 45 ... 115 ms Between Coil Energization and NO Contact Closing 50 ... 120 ms
Connecting Capacity Main Circuit	Bar 52 mm ² Rigid Al-Cable 3x185 mm ² Rigid Cu-Cable 300 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 1 x 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars

Technical UL/CSA

NEMA Size	7
Horsepower Rating NEMA	(230 V AC) Three Phase 300 Hp (460 V AC) Three Phase 600 Hp (575 V AC) Three Phase 600 Hp
Maximum Operating Voltage UL/CSA	Main Circuit 1000 V
General Use Rating UL/CSA	(1000 V AC) 900 A (600 V AC) 900 A
Horsepower Rating UL/CSA	(200 V AC) Three Phase 250 hp (208 V AC) Three Phase 250 hp (220 ... 240 V AC) Three Phase 300 hp (440 ... 480 V AC) Three Phase 600 hp (550 ... 600 V AC) Three Phase 700 hp

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 U_c) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U_c) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C
Maximum Operating	Without Derating 3000 m

Altitude Permissible

Resistance to Shock acc.
to IEC 60068-2-27

Shock Direction: A 5 g
Shock Direction: B1 5 g
Shock Direction: B2 5 g
Shock Direction: C1 5 g
Shock Direction: C2 5 g

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

ABS Certificate	15-LD1408622-PDA
BV Certificate	BV_13409-C0BV
CB Certificate	SE-82863
CCS Certificate	GB14T00030
CQC Certificate	CQC2007010304256684 CQC2012010304540080
CSA Certificate	306712-1
Declaration of Conformity - CCC	2020980304001301 2020980304001045
Declaration of Conformity - CE	2CMT2019-005796
Declaration of Conformity - UKCA	2CMT2020-006118
DNV Certificate	DNV_E-10966
DNV GL Certificate	TAE00001W1
EAC Certificate	9AKK107046A8618
GL Certificate	GL_42988-02HH
LOVAG Certificate	SE-0114206
LR Certificate	16-20064
PRS Certificate	TE_2092_880423_16
RINA Certificate	ELE060313XG_002
RMRS Certificate	9AKK107045A6978
UL Certificate	UL_20111101-E36588
UL Listing Card	UL_E36588

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Depth / Length	375 mm
Package Level 1 Height	310 mm
Package Level 1 Gross Weight	15 kg
Package Level 1 EAN	7320500220405

Classifications

Object Classification Code		Q
ETIM 4	EC000066 - Magnet contactor, AC-switching	
ETIM 5	EC000066 - Magnet contactor, AC-switching	
ETIM 6	EC000066 - Power contactor, AC switching	
ETIM 7	EC000066 - Power contactor, AC switching	
ETIM 8	EC000066 - Power contactor, AC switching	
eClass	V11.0 : 27371003	
UNSPSC	39121529	
IDEA Granular Category Code (IGCC)	4758 >> lec Contactors	
E-Number (Norway)	4115299	
E-Number (Sweden)	3228364	

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SFN170801R1001	RU19/120 LVRT-Module	RU19/120	1	piece
1SFN170801R1002	RU19/240 LVRT-Module	RU19/240	1	piece

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF750

