



PRODUCT-DETAILS

RBR121-24VUC

RBR121-24VUC Interface relay R600 1c/o,A1-A2=24VAC/DC,5-250VAC/60mA-6A



General Information

Extended Product Type	RBR121-24VUC
Product ID	1SNA645501R0500
EAN	4013614508172
Catalog Description	RBR121-24VUC Interface relay R600 1c/o,A1-A2=24VAC/DC,5-250VAC/60mA-6A

Long Description

The RBR121-24VUC is a boxed interface relay with spring terminals, which can be seamlessly snap-on mounted onto a DIN Rail. The relay is soldered into device housing, ensuring a high resistance against vibration and this is further enhanced by the spring terminals which improve contact reliability by automatically adjusting the tension to the wire gauge. This relay operates with a 24 V AC/DC rated control supply voltage and has a 1 c/o (SPDT) output with contacts rated at 250 V / 6 A. This 6mm wide boxed interface relay may be used for electrical isolation, amplification and signal matching and enables the switching of high currents on a small footprint. It has an integrated LED, which provides the visual indication of the energization of the relay coil and UL 94-V0 certified device housing, improving safety by providing high levels flame retardation. Jumper bars are available as accessories.

Ordering

EAN	4013614508172
Minimum Order Quantity	10 piece
Customs Tariff Number	85364900

Popular Downloads	
Data Sheet, Technical Information	2CDC110004C0210_05
Instructions and Manuals	1SVC645000M9000
CAD Dimensional Drawing	2CDC001079B0201

Dimensions	
Product Net Width	6 mm
Product Net Height	67.5 mm
Product Net Depth / Length	75 mm
Product Net Weight	0.02 kg

Technical	
Function	Boxed interface relay R600
Sub-Function	Relay with built in LED
Rated Control Supply Voltage (U _s)	24 V AC/DC
Output	1 c/o (SPDT) contact
Output Signal	5 ... 250VAC / 60mA ... 6A
Terminal Type	Spring Terminals
Degree of Protection	IP20
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60947-5-1 UL 508

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
RoHS Information	1SVD982016-0001
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations	
CB Certificate	CB DK-53188-UL
CCC Certificate	CCC_2017010303941444
CQC Certificate	CQC_2017010303941444
CSA Certificate	CSA_254821
cUR Certificate	cUR_E352056
Declaration of Conformity - CCC	CCC_2020980303000254
Declaration of Conformity - CE	1SVD982016-0001
Declaration of Conformity - UKCA	1SVD982016-1000
EAC Certificate	EAC_RU_C-FR.ME77.B.01634
LR Certificate	LR_16_20068
UR Certificate	UR_E352056

Container Information	
------------------------------	--

Package Level 1 Units	box 10 piece
Package Level 1 Width	73 mm
Package Level 1 Depth / Length	80 mm
Package Level 1 Height	71 mm
Package Level 1 Gross Weight	0.23 kg
Package Level 1 EAN	3472596455019

Classifications

Object Classification Code	K
ETIM 7	EC001437 - Switching relay
ETIM 8	EC001437 - Switching relay
ETIM 9	EC001437 - Switching relay
eClass	V11.0 : 27371601
UNSPSC	39122331
E-Number (Sweden)	4001139

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

