



PRODUCT-DETAILS

CE4T-10B-11

CE4T-10B-11 Machine Stop



General Information	
Extended Product Type	CE4T-10B-11
Product ID	1SFA619550R1076
EAN	7320500260845
Catalog Description	CE4T-10B-11 Machine Stop
Long Description	The CE4T-10B-11 Machine Stop is: Compact - Machine Stop - Twist release - Maintained - Mushroom 40 mm - Black - Non-illuminated - 1NO+1NC - 1 NO - 1 NC - 24 ... 300 V This Machine Stop is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost. <u>The compact range has a high level of dust and water resistance.</u>

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	8536500000

Popular Downloads	
Data Sheet, Technical Information	1SFC151007C02__
Instructions and Manuals	1SFC151011M0201

Dimensions

Product Net Width	0.04 m
Product Net Height	0.04 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.038 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Black
Actuator Type	Mushroom 40 mm
Bezel Material	n/a
Illumination	Non-illuminated
Function	Maintained
Sub-Function	Twist release
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 ... 300 V
Rated Operational Current DC-13 (I _θ)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _θ)	(240 V) 1 A
Power Loss	Maximum 5 W
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm² Flexible with Ferrule 2 x 0.5...1.5 mm² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm² Flexible 1 x 0.5 ...1.5 mm² Flexible 2 x 0.5 ...1.5 mm² Solid 1 x 0.5...1.5 mm² Solid 2 x 0.5...1.5 mm²
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA

Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental

Degree of Protection

Front IP66
Front IP67
Front IP69K
Terminals IP20

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
SCIP	c9d2b28b-6b2a-4e6f-bfa9-99c3079b3320 Sweden (SE)
Simplified SCIP	9bbc453a-89c4-489a-abd8-0f7b3dc9c2b4 Germany (DE) 7eb2ab47-251d-417c-810e-b35e6efe76be Spain (ES) 5bc9dbb0-bf7c-4b5e-b174-6bc5f4df7549 Hungary (HU) bcd92f88-15b6-4e52-9fa9-3aec4d40ae04 Croatia (HR) 33e3cf44-2efa-4c77-a69c-459df5c33f3b Germany (DE) 222c513a-bcdb-486e-a4c4-1be778ca2cb2 Finland (FI) dc043c01-46af-469f-acc2-8f7f5d9dbcbc Italy (IT) 7c95ce49-308d-41a6-9c61-79c26bb31e78 Germany (DE) 43823b6d-de3a-4296-bfe1-e18fb22e81d3 Belgium (BE) 618b5469-cb20-4d9f-a987-1fac2233c2b7 Denmark (DK) 8b7cacf1-a041-4390-8c91-c3179d326a01 Poland (PL) 6a815069-d267-45d4-87da-c19c2eb8a533 Norway (NO) a89b3991-1f70-44c0-8aff-6c5f07f58c4d Czech Republic (CZ) 5ac05d40-90bf-4c0e-a60d-fef1ac3fe4ee Estonia (EE) 45ef9385-e6e7-4f68-8e25-252f314dd11f Netherlands (NL) 3325033f-c692-4c70-9d51-1685c14f8145 Poland (PL) 46354e37-b3ac-40de-ac55-cc49c4942417 Hungary (HU) 5e3d2d67-5c76-4887-93b8-52d2272d507d Portugal (PT) 4d808e42-c5f4-477f-b918-cca824136ab0 Greece (GR) 587c82d7-c83b-4ac8-bcf1-27c09bed3ace Bulgaria (BG) e5dc14aa-708f-44e0-b486-84a6428d7a97 Sweden (SE) 3b142252-b531-4028-ac71-481be9d0187c France (FR) fd46f59f-9fa2-4afa-8488-0002a03d9361 Poland (PL) 8d9cca03-10d7-45d8-9efc-6d6170eee407 Germany (DE) b90685cb-f4b9-4fd8-b523-2ebbc8892017 France (FR) 3b436f36-6d2c-4325-9193-d0a9fc4c3b01 Germany (DE) 7d912618-dd44-4568-87b1-0ad716703263 Belgium (BE)
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

CB Certificate	CN54150
CQC Certificate	CQC2003010305054693
cULus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Declaration of Conformity - CE	2CMT2019-005802
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC RU C-CN.ME77.B.00537/19

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	0.165 m
Package Level 1 Depth / Length	0.09 m

Package Level 1 Height	0.045 m
Package Level 1 Gross Weight	0.04 kg
Package Level 1 EAN	7320500260845

Classifications

Object Classification Code	S
ETIM 6	EC002034 - Emergency stop complete
ETIM 7	EC001028 - Push button, complete
ETIM 8	EC001028 - Push button, complete
eClass	V11.0 : 27371228
UNSPSC	39122216
IDEA Granular Category Code (IGCC)	5212 >> Push button for distribution board
E-Number (Finland)	2312174
E-Number (Sweden)	3711560

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CE Compact Emergency Stops and Machine Stops
Low Voltage Products and Systems → Control Products → Pilot Devices → Emergency Stop and Safety Stop

