



PRODUCT-DETAILS

C3SS3-10B-02

C3SS3-10B-02 Selector Switch



General Information	
Extended Product Type	C3SS3-10B-02
Product ID	1SFA619212R1056
EAN	7320500555569
Catalog Description	C3SS3-10B-02 Selector Switch
Long Description	The C3SS3-10B-02 Selector Switch is: Compact - Selector Switch - 3-position - Maintained/Momentary - Short handle - Black - Non-illuminated - Black Plastic - 2NC - 0 NO - 2 NC - 300 V This Selector Switch is part of ABB's compact range, the most efficient all-in-one solution available, reducing installation time and cost. <u>The compact range has a high level of dust and water resistance.</u>

Ordering	
Minimum Order Quantity	10 piece
Customs Tariff Number	8536501999

Popular Downloads	
Data Sheet, Technical Information	1SFC151007C02__

Dimensions

Product Net Width	0.03 m
Product Net Height	0.03 m
Product Net Depth / Length	0.072 m
Product Net Weight	0.024 kg

Technical

Ambient Air Temperature	Operation -25 ... +70 °C Storage -40 ... +85 °C
Color	Black
Actuator Type	Short handle
Bezel Material	Black Plastic
Illumination	Non-illuminated
Function	Maintained/Momentary
Sub-Function	3-position
Maintained Positions	A, B
Spring Return From	C to B
Number of Auxiliary Contacts NC	2
Number of Auxiliary Contacts NO	0
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	Maximum 300 V
Rated Operational Current DC-13 (I _θ)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _θ)	(24 / 127 V) 1.5 A (220 / 240 V) 1 A
Power Loss	Maximum 5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm² Flexible with Ferrule 2 x 0.5...1.5 mm² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm² Flexible 1 x 0.5 ...1.5 mm² Flexible 2 x 0.5 ...1.5 mm² Solid 1 x 0.5...1.5 mm² Solid 2 x 0.5...1.5 mm²
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA

Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Environmental	
Degree of Protection	Front IP66 Front IP67 Front IP69K Terminals IP20

Material Compliance	
Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2022-006479
RoHS Information	2CMT2022-006498
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006523
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations	
CB Certificate	CQC_CN_CN50749
CQC Certificate	CQC2003010305054693
cURus Certificate	UL E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Declaration of Conformity - CE	2CMT2015-005451
Declaration of Conformity - UKCA	2CMT2020-006121
DNV GL Certificate	9AKK107046A3749
EAC Certificate	RU C-CN.ME77.B.00587/20

Container Information	
Package Level 1 Units	bag 10 piece
Package Level 1 Width	0.235 m
Package Level 1 Depth / Length	0.125 m
Package Level 1 Height	0.035 m
Package Level 1 Gross Weight	0.24 kg
Package Level 1 EAN	7320500247204

Classifications	
Object Classification Code	S
ETIM 6	EC001029 - Selector switch, complete
ETIM 7	EC001029 - Selector switch, complete
ETIM 8	EC001029 - Selector switch, complete
eClass	V11.0 : 27371243
UNSPSC	39121500
E-Number (Finland)	2312922
E-Number (Norway)	4372700
E-Number (Sweden)	3705581

Categories

Low Voltage Products and Systems → Control Products → Pilot Devices → Compact Range → CSS Compact Selector Switches

