



PRODUCT-DETAILS

F204 AC-25/0.1-L

F204 AC-25/0.1-L Residual Current Circuit Breaker 4P Type AC 100 mA



| General Information | |
|-----------------------|--|
| Extended Product Type | F204 AC-25/0.1-L |
| Product ID | 2CSF204023R2250 |
| EAN | 8012542816201 |
| Catalog Description | F204 AC-25/0.1-L Residual Current Circuit Breaker 4P Type AC 100 mA |
| Long Description | The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is suitable for installations where neutral on the left is . |

| ABB EcoSolutions | |
|------------------|-----|
| ABB EcoSolutions | Yes |

| Circular Value | |
|-------------------------------|---|
| Circular Design | Design for Closing Resource Loops - Standard EN45555 - 52.5 % |
| Principles Recyclability Rate | |

Eco Transparency

Environmental Product
Declaration - EPD

9AKK108467A3700

Technical

| | |
|--|--|
| Standards | IEC/EN 61008 |
| Type of Residual Current | Type AC |
| Rated Voltage (U _r) | 230/400 V |
| Rated Operational Voltage | 230 / 400 V AC |
| Rated Insulation Voltage (U _i) | 500 V |
| Rated Impulse Withstand Voltage (U _{imp}) | 4 kV |
| Rated Current (I _n) | 25 A |
| Rated Residual Current | 100 mA |
| Rated Conditional Short-Circuit Current (I _{nc}) | 10 kA |
| Rated Service Short-Circuit Breaking Capacity (I _{cs}) | 1 kA |
| Maximum Surge Current | 0.25 kA |
| Leakage Current Type | AC |
| Rated Frequency (f) | 50 ... 60 Hz |
| Power Loss | at Rated Operating Conditions per Pole 1.3 W |
| Power Supply Connection | Arbitrary |
| Electrical Endurance | 10000 cycle |
| Number of Poles | 4 |
| Operating Characteristic | Instantaneous |
| Position of Neutral Terminals | Left |
| Mounting Type | DIN-Rail |
| Options Provided | None |
| Accessories Available | Yes |
| Connecting Capacity | Busbar 10 mm ² Rigid 25 ... 25 mm ² Flexible 25 ... 25 mm ² |
| Rated Cross-Section | 4 - Multi-Wired 0...25 mm ² 1 - Solid-Core 25...25 mm ² |

Material Compliance

| | |
|---|--|
| RoHS Information | 9AKK106713A5602 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| RoHS Date | 20211115 |
| REACH Declaration | 9AKK108467A9482 |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A3363 |

| Environmental | |
|--|---|
| Ambient Temperature | -25...55 °C |
| Ambient Air Temperature | Operation -25...55 °C |
| Degree of Protection | IP2X |
| Pollution Degree | 2 |
| Resistance to Vibrations | 20 Cycles with Load 0.8 In: 1g or 1mm 50 ... 150 ... 5 Hz |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g 2 shocks 13 ms |
| Environmental Information | Refer to RoHS |

| Technical UL/CSA | |
|-------------------------------------|--------|
| Short-Circuit Current Rating (SCCR) | 100 mA |

| Dimensions | |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 4 |
| Product Net Width | 0.070 m |
| Product Net Height | 0.085 m |
| Product Net Depth / Length | 0.069 m |
| Product Net Weight | 0.360 kg |
| Built-In Depth (t ₂) | 69 mm |

| Ordering | |
|------------------------------|-------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Gross Weight | 0.415 kg |

| Certificates and Declarations | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK106713A5602 |

| Installation | |
|--------------------------|-----------------|
| Instructions and Manuals | 9AKK107991A6127 |

| Popular Downloads | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 9AKK107991A8329 |

| Classifications | | | | |
|----------------------------|--|--|--|--|
| ETIM 8 | EC000003 - Residual current circuit breaker (RCCB) | | | |
| ETIM 9 | EC000003 - Residual current circuit breaker (RCCB) | | | |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) | | | |
| WEEE B2C / B2B | Business To Consumer | | | |
| CN8 | 85363030 | | | |
| eClass | V11.0 : 27142201 | | | |
| Object Classification Code | F | | | |

| Accessories | | | | |
|-----------------|--------------------------------------|---------------|----------|-----------------|
| Identifier | Description | Type | Quantity | Unit Of Measure |
| 2CDS200912R0001 | S2C-H6R Auxiliary Contact | S2C-H6R | 2 | piece |
| 2CDS200922R0001 | S2C-S/H6R Signal / Auxiliary Contact | S2C-S/H6R | 2 | piece |
| 2CDS200946R0001 | S2C-H6-11R Auxiliary Contact | S2C-H6-11R | 1 | piece |
| 2CDS200946R0003 | S2C-H6-02R Auxiliary Contact | S2C-H6-02R | 1 | piece |
| 2CDS200946R0002 | S2C-H6-20R Auxiliary Contact | S2C-H6-20R | 1 | piece |
| 2CSS200933R0011 | F2C-A1 Shunt trip | F2C-A1 | 1 | piece |
| 2CSS200933R0012 | F2C-A2 Shunt trip | F2C-A2 | 1 | piece |
| 2CSS200911R0005 | S2C-UA 230 AC Undervoltage Release | S2C-UA 230 AC | 1 | piece |
| 2CSS200911R0007 | S2C-UA 24 DC Undervoltage Release | S2C-UA 24 DC | 1 | piece |
| 2CSS200911R0002 | S2C-UA 24 AC Undervoltage Release | S2C-UA 24 AC | 1 | piece |
| 2CSS200911R0008 | S2C-UA 48 DC Undervoltage Release | S2C-UA 48 DC | 1 | piece |
| 2CSS200911R0004 | S2C-UA 110 AC Undervoltage Release | S2C-UA 110 AC | 1 | piece |
| 2CSS200911R0006 | S2C-UA 400 AC Undervoltage Release | S2C-UA 400 AC | 1 | piece |
| 2CSS200911R0001 | S2C-UA 12 DC Undervoltage Release | S2C-UA 12 DC | 1 | piece |
| 2CSS200911R0010 | S2C-UA 230 DC Undervoltage Release | S2C-UA 230 DC | 1 | piece |
| 2CSS200911R0009 | S2C-UA 110 DC Undervoltage Release | S2C-UA 110 DC | 1 | piece |
| 2CSS200911R0003 | S2C-UA 48 AC Undervoltage Release | S2C-UA 48 AC | 1 | piece |
| 2CSS200910R0005 | S2C-OVP1 Overvoltage Release | S2C-OVP1 | 1 | piece |
| 2CSS200993R0005 | S2C-OVP2 Overvoltage Release | S2C-OVP2 | 1 | piece |
| 2CSF200997R0013 | F2C-CM Motor operating device | F2C-CM | 1 | piece |
| 2CSF200996R0013 | F2C-ARI Auto-reclosing unit | F2C-ARI | 1 | piece |

| Categories | |
|--|--|
| Low Voltage Products and Systems → Modular DIN Rail Products → Residual Current Devices RCDs → Residual Current Devices RCDs | |

