




PRODUCT-DETAILS

GF1325-20-22-51

GF1325-20-22-51 Contactor



General Information

Extended Product Type	GF1325-20-22-51
Product ID	1SFL647731R5122
EAN	7320500540947
Catalog Description	GF1325-20-22-51 Contactor
Long Description	A 2-phase Contactor suitable for PV solar power applications up to max 1500V DC. Operated with wide voltage range 24-60V DC/AC 50/60Hz

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	8536490099

Popular Downloads

Data Sheet, Technical Information	1SBC100218B0201
Instructions and Manuals	1SFC100003M0001
CAD Dimensional Drawing	2CDC001079B0201

Dimensions	
Product Net Width	253 mm
Product Net Depth / Length	300 mm
Product Net Height	355 mm
Product Net Weight	14.3 kg

Technical	
Number of Main Contacts NO	2
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	2
Number of Auxiliary Contacts NC	2
Rated Operational Voltage	Main Circuit 1500 V
Rated Frequency (f)	Control Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 1375 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 7920 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 1740 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 4750 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 9500 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 6340 A
Maximum Electrical Switching Frequency	15 cycles per hour
Rated Operational Current DC-1 (I _e)	(1500 V DC) 2-Pole, 40 °C 101 A
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1500 V acc. to UL/CSA 1500 V
Rated Impulse Withstand Voltage (U _{imp})	Main Circuit 8 kV
Mechanical Durability	50000 cycle
Maximum Mechanical Switching Frequency	60 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U _c Min. ... 1.1 x U _c Max. (at $\theta \leq 70\text{ °C}$)
Rated Control Circuit Voltage (U _c)	50 Hz 24...60 V 60 Hz 24...60 V DC Operation 24 ... 60 V
Operate Time	Between Coil De-energization and NO Contact Opening 33...70 ms Between Coil Energization and NO Contact Closing 50...120 ms
Connecting Capacity Main Circuit	Solid 600 mm²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm² Flexible 2x0.75 ... 2.5 mm² Solid 2x1 ... 4 mm² Stranded 2x1 ... 4 mm²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Terminal Type	Main Circuit: Bars
Rated Operational Current DC-PV3 (I _e)	(1500 V DC) 2-Pole, 60 °C 1325 A (1500 V DC) 2-Pole, 70 °C 1050 A

Technical UL/CSA	
Maximum Operating Voltage UL/CSA	Main Circuit 1500 V

Environmental

Ambient Air Temperature	Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C Close to Contactor for Storage -40 ... 70 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	2CMT2021-006202
RoHS Information	2CMT2021-006277
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006525
WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

ABS Certificate	9AKK108466A1583
BV Certificate	9AKK108466A6837
CB Certificate	1SFC100042D0101
CQC Certificate	CQC20012271919
Declaration of Conformity - CCC	2020980304002803
Declaration of Conformity - CE	1SFC100019D2701
Declaration of Conformity - UKCA	2CMT2020-006118
DNV Certificate	9AKK108466A1584
LR Certificate	9AKK108466A2274
UL Certificate	1SFC100021D0101

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	402 mm
Package Level 1 Depth / Length	305 mm
Package Level 1 Height	415 mm
Package Level 1 Gross Weight	16.45 kg

Classifications

ETIM 6	EC002552 - Power contactor, DC switching
ETIM 7	EC002552 - Power contactor, DC switching
ETIM 8	EC002552 - Power contactor, DC switching
eClass	V11.0 : 27371018
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4763 >> Power contactor, DC switching
E-Number (Norway)	4115804

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → GF Contactors → GF1325

