



PRODUCT-DETAILS

IB132-G

IB132-G Enclosure, GY/BK, IP65 Standard version, 3 times lockable



General Information	
Extended Product Type	IB132-G
Product ID	1SAM201911R1010
EAN	4013614421617
Catalog Description	IB132-G Enclosure, GY/BK, IP65 Standard version, 3 times lockable
Long Description	IB132-G enclosure is suitable for manual motor starter MS116/MS132. The combination of manual motor starter and enclosure allows to setup all required control and protection functions for single machine installations. The enclosure has a IP65 degree of protection. Additional mounting of auxiliary and signalling contacts, shunt trips and undervoltage release is possible. The handle is up to 3-times lockable in OFF position.

Ordering	
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Popular Downloads	
Data Sheet, Technical	1SBC100173C0201

Information

Instructions and Manuals	2CDC131028M6805
CAD Dimensional Drawing	2CDC001079B0201
Dimension Diagram	1SAM200441F0001

Dimensions

Product Net Width	118 mm
Product Net Height	194 mm
Product Net Depth / Length	119 mm
Product Net Weight	0.37 kg

Technical

Contact Position Indication	ON / OFF / TRIP
Actuator Type	Rotary Handle
Color	grey / black
Degree of Protection	IP65
Standards	CSA 22.2 No. 14 IEC/EN 60947-1 IEC/EN 60947-4-1 UL 508
Product Name	Enclosure
Suitable For	MS116 MS132
Suitable for Product Class	Manual Motor Starter
Accessory Group	Mechanical
Accessory Type	Enclosure
Remarks	For detailed specification see installation instruction

Technical UL/CSA

Enclosure Type UL/CSA	12
-----------------------	----

Environmental

Ambient Air Temperature	Operation 0 ... +40 °C Storage -50 ... +80 °C
-------------------------	--

Material Compliance

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
REACH Declaration	1SAA963005-4502
RoHS Information	1SAA963006-4502
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA	2CMT2023-006539

WEEE B2C / B2B	Business To Business
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Certificates and Declarations

cUL Certificate	cUL_E137861
Declaration of Conformity - CE	1SAD101100-3411
Declaration of Conformity - UKCA	1SAD201100-3411
UL Certificate	UL_E137861

Container Information

Package Level 1 Width	129 mm
Package Level 1 Depth / Length	200 mm
Package Level 1 Height	129 mm
Package Level 1 Gross Weight	0.435 kg
Package Level 1 EAN	4013614421617
Package Level 1 Units	box 1 piece

Classifications

Object Classification Code	U
ETIM 4	EC002498 - Accessories for low-voltage switch technology
ETIM 5	EC000712 - Empty enclosure for switchgear
ETIM 6	EC000712 - Empty enclosure for switchgear
ETIM 7	EC000712 - Empty enclosure for switchgear
ETIM 8	EC000712 - Empty enclosure for switchgear
eClass	V11.0 : 27371301
UNSPSC	39121334
IDEA Granular Category Code (IGCC)	4492 >> Modular electrical enclosure
E-Number (Finland)	3705861
E-Number (Sweden)	3112073

Categories

Low Voltage Products and Systems → Circuit Breakers → Manual Motor Starters

Low Voltage Products and Systems → Control Products → Manual Motor Starters → Manual Motor Starters

