6122/02-81-500 1/3



PRODUCT-DETAILS

6122/02-81-500

Horizontal 0 ... 180 ° Solo anthracite



General Information	
Extended Product Type	6122/02-81-500
Product ID	2CKA006132A0283
EAN	4011395140604
Catalog Description	Horizontal 0 180 ° Solo anthracite
Long Description	For ABB i-bus® KNX 6120/12-101, 6120/13. Movement detector with up to 4 channels. Incl. 10 logic channels (light scene actuator, seguence actuator, logic gates, etc.).

Installation	
Instructions and Manuals	2CKA000173B7414
Mounting Type	Flush Mounted
Mounting Position	vertical
Mounting Height	Optimum 0.8 1.2 m

Technical	
Data Sheet, Technical Information	DEBJE-th_KNX_Bedienelemente_ABB_FR_V1-Spec
Measuring Range	6 m

6122/02-81-500 2/3

Number of Channels	4		
Compatible Bus Systems	KNX (TP)		
Product Range	KNX		
Minimum Switching Time	Switch-On 10 second [unit of time]		
Number of Batteries	C		
Design			
Design Range	63x63		
	future linear Busch-axcent Busch-axcent pur Busch-Dynasty		
Surface Finishing	cara		
	Glossy		
Material	Thermoplastic		
RAL Number	RAL 7021 - Black Grey		
Color	anthracite anthracite		
Material Compliance			
RoHS Information	2CKA200000E4485		
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019		
REACH Declaration	2CKA309999E9999		
REACH Information	False - does not contains substances > 0.1 mass percentage		
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363		
Reporting Template	Operation -5 +45 °C		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection	Operation -5 +45 °C		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions	Operation -5 +45 °C IP20		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width	Operation -5 +45 °C IP20		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions	Operation -5 +45 °C IP20 63 mm 63 mm		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width Product Net Height Product Net Depth /	Operation -5 +45 °C IP20 63 mm 63 mm 40 mm		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width Product Net Height Product Net Depth / Length	Operation -5 +45 °C IP20 63 mm 63 mm 40 mm		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight Built-In Depth (t ₂)	Operation -5 +45 °C IP20 63 mm 63 mm 40 mm		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight Built-In Depth (t ₂) Certificates and Declarations	Operation -5 +45 °C IP20 63 mm 63 mm 40 mm 35 g 33 mm		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight Built-In Depth (t ₂)	Operation -5 +45 °C IP20 63 mm 63 mm 40 mm 35 g 33 mm		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight Built-In Depth (t ₂) Certificates and Declarations Declaration of Conformity -CE	Operation -5 +45 °C IP20 63 mm 63 mm 40 mm 35 g 33 mm		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight Built-In Depth (t ₂) Certificates and Declarations Declaration of Conformity -CE Classifications	Operation -5 +45 °C IP20 63 mm 63 mm 40 mm 35 g 33 mm		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight Built-In Depth (t ₂) Certificates and Declarations Declaration of Conformity - CE Classifications ETIM 9	Operation -5 +45 °C IP20 63 mm 63 mm 40 mm 35 g 33 mm 2CKA100000E1012		
Reporting Template (CMRT) Environmental Ambient Air Temperature Degree of Protection Dimensions Product Net Width Product Net Height Product Net Depth / Length Product Net Weight Built-In Depth (t ₂) Certificates and Declarations Declaration of Conformity -CE Classifications	9AKK108468A3363 Operation -5 +45 °C IP20 63 mm 63 mm 40 mm 35 g 33 mm 2CKA100000E1012 EC001582 - Movement sensor for bus system V11.0 : 27143144 5. Small Equipment (No External Dimension More Than 50 cm)		

6122/02-81-500 3/3

Accessories				
Identifier	Description	Туре	Quantity	Unit Of Measure
2CKA006120A0075	6120/12-101-500 Bus coupler, FM	6120/12-101- 500	1	piece
2CKA006120A0072	6120/13-500 Power bus coupler, FM	6120/13-500	1	piece

Categories

Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow Presence Detection \rightarrow Motion Detectors Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow Presence Detection \rightarrow Presence Detectors Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow User Operation \rightarrow Busch-balance SI / Basic 55 for Push Button Coupling Units \rightarrow Motion Detectors Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow User Operation \rightarrow Reflex SI / Busch-Duro 2000SI for Push Button Coupling Units \rightarrow Motion Detectors Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow User Operation \rightarrow Solo \rightarrow Motion Detectors Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow User Operation \rightarrow Solo / Alpha for Push Button Coupling Units \rightarrow Motion Detectors

