



PRODUCT-DETAILS

6179/02-204-500

Horizontal 0 ... 220 ° Presence Detection alpine white



| General Information | | | |
|-----------------------|---|--|--|
| Extended Product Type | 6179/02-204-500 | | |
| Product ID | 2CKA006132A0317 | | |
| EAN | 4011395168615 | | |
| Catalog Description | Horizontal 0 220 ° Presence Detection alpine whi | | |
| Long Description | With 4 movement channels. With 1 twilight / brightness channel with 3 switching thresholds. With 1 temperature channel with three switching thresholds. With 7- channel IR remote control. Remote control possible via IR remote control KNX 6179 (included in scope of delivery). With integrated KNX bus coupler. No additional power supply necessary. Surveillance density: 92 sectors with 368 switching segments. Twilight sensor: approx. 1 - 1000 lux Brightness sensor: approx. 1 - 80 klux. Temperature sensor: approx25 to +55 °C Switch-off delay: approx. 10 sec to 1092 min Sensor angle: 220° Range: approx. 16 m | | |

| Installation | | | | |
|-----------------------------|-----------------|--|--|--|
| Instructions and Manuals | 2CKA000073B7898 | | | |
| Mounting Type | Surface Mounted | | | |
| Mounting Position | Wall | | | |
| Mounting Height | Optimum 2.5 m | | | |

© 2024 ABB. All rights reserved.

2024/04/12

Subject to change without notice

| Technical | |
|---|---|
| Data Sheet, Technical | 2CKA001373B803 |
| Information | |
| Function | Activating/deactivating 2-zone operation |
| | Activating/deactivating twilight switch operation Adjusting the sensitivit |
| | Brightness senso |
| | Build-in RTC |
| | Logic functions Temperature senso |
| | Twilight sensor |
| Number of Channels | 2 |
| Compatible Bus Systems | KNX (TP |
| Product Range | KN |
| Minimum Switching Time | Switch-On 10 second [unit of time] |
| Battery Chemical Composition | Lithium |
| Battery Type | Button Cel |
| Battery Weight | 2.5 g |
| Number of Batteries | : |
| | |
| Design | |
| Surface Finishing | Untreated Mat |
| Material | Thermoplastic |
| RAL Number | RAL 9016 - Traffic White |
| Color | alpine white |
| | |
| Material Compliance | |
| RoHS Information | 2CKA200000E4499 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| REACH Declaration | 2CKA309999E9999 |
| REACH Information | True - contains substances > 0.1 mass percentage |
| Conflict Minerals Reporting Template (CMRT) | 9AKK108468A336: |
| | |
| Environmental | |
| Ambient Air Temperature | Operation -25 +55 °C |
| Degree of Protection | IP55 |
| Dimensions | |
| Product Net Width | 125 mm |
| Product Net Height | 115 mm |
| Product Net Depth / Length | 141 mm |
| Product Net Weight | 317 ç |
| | |

© 2024 ABB. All rights reserved.

2024/04/12

Subject to change without notice

Built-In Depth (t₂)

Ordering

Replacement Product ID (NEW)

Certificates and Declarations

Declaration of Conformity - CE 2CKA100000E1028

2CKA006132A0427

0 mm

| Classifications | | | |
|-----------------|--|--|--|
| ETIM 9 | EC001582 - Movement sensor for bus system | | |
| eClass | V11.0 : 27143144 | | |
| UNSPSC | 39121801 | | |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) | | |
| WEEE B2C / B2B | Business To Consumer | | |

Accessories

| Identifier | Description | Type Quantity | | Unit Of Measure |
|-----------------|--|---------------|---|--------------------|
| 2CKA006132A0320 | Presence Detection grey / anthracite | 6179-500 | 1 | piece |
| 2CKA006800A2562 | MasterLINE Ceiling/Corner Adapter white 68 | 368-204-500 | 1 | piece |

Categories







© 2024 ABB. All rights reserved.