6122/10-212-500 1/3



PRODUCT-DETAILS

6122/10-212-500

Horizontal 0 ... 180 ° Reflex SI / Busch-Duro 2000SI for Push Button Coupling Units white



| General Information | |
|-----------------------|---|
| Extended Product Type | 6122/10-212-500 |
| Product ID | 2CKA006132A0373 |
| EAN | 4011395211236 |
| Catalog Description | Horizontal 0 180 ° Reflex SI / Busch-Duro 2000SI for Push Button Coupling Units white |
| Long Description | Movement detector with up to 4 channels. The bus can be connected via enclosed terminal block. With integrated KNX bus coupler. |

| Installation | | |
|--------------------------|--------------------|--|
| Instructions and Manuals | No document needed | |
| Mounting Type | Flush Mounted | |
| Mounting Position | vertical | |
| Mounting Height | Optimum 1.1 m | |

| Technical | |
|--------------------------------------|-----------------|
| Data Sheet, Technical Information | 2CKA001373B8910 |
| Compatible Bus Systems | KNX (TP) |

6122/10-212-500 2/3

| Product Range | KNX |
|--------------------------------------|--|
| Minimum Switching Time | Switch-On 10 second [unit of time] |
| Number of Batteries | 0 |
| | |
| Design | |
| | B 1 B 2000 |
| Design Range | Busch-Duro 2000 Busch-Duro 2000 SI Linear |
| Material | Thermoplastic |
| Color | white |
| | |
| Material Compliance | |
| RoHS Information | 2CKA200000E4544 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| REACH Declaration | 2CKA309999E9999 |
| REACH Information | False - does not contains substances > 0.1 mass percentage |
| Conflict Minerals | 9AKK108468A3363 |
| Reporting Template (CMRT) | |
| | |
| Environmental | |
| Ambient Air Temperature | Operation -5 +45 °C |
| Degree of Protection | IP20 |
| Dimensions | |
| - | E4 mm |
| Product Net Width Product Net Height | 54 mm 54 mm |
| Product Net Depth / | 29 mm |
| Length | 23 11111 |
| Product Net Weight | 52 <u>a</u> |
| Contification and Deployations | |
| Certificates and Declarations | |
| Declaration of Conformity - CE | 2CKA100000E1084 |
| Declaration of Conformity - UKCA | 2CKA400000E0213 |
| | |
| Classifications | |
| ETIM 9 | EC000138 - Sensor element for movement sensor |
| eClass | V11.0 : 27144008 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |

6122/10-212-500 3/3

Categories

Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow Presence Detection \rightarrow Motion Detectors Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow Presence Detection \rightarrow Presence Detectors Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow User Operation \rightarrow Busch-balance SI / Basic 55 for Push Button Coupling Units \rightarrow Motion Detectors

Low Voltage Products and Systems \to Building and Home Automation Solutions \to KNX \to User Operation \to Reflex SI / Busch-Duro 2000SI for Push Button Coupling Units \to Motion Detectors

Low Voltage Products and Systems \rightarrow Building and Home Automation Solutions \rightarrow KNX \rightarrow User Operation \rightarrow Solo / Alpha for Push Button Coupling Units \rightarrow Motion Detectors

