6320/30-24G-500 1/3



PRODUCT-DETAILS

6320/30-24G-500 6320/30-24G-500 triton 3/6gang MF/IR



General Information	
Extended Product Type	6320/30-24G-500
Product ID	2CKA006320A0014
EAN	4011395138854
Catalog Description	6320/30-24G-500 triton 3/6gang MF/IR
Long Description	With integrated KNX bus coupler. With labelling field. Rocker switch left/right (switching/dimming/blind/value sender/light scenes/fan function).
Installation	
Instructions and Manuals	DED IF he 72 1 7426 6220 500 Man
Mounting Type	DEBJE-ba_73_1_7426_6320-500-Man Flush Mounted
Modified 1796	Tush wounted
Technical	
Data Sheet, Technical Information	2CKA001473B8838
Number of Actuation Points	3
Compatible Bus Systems	KNX (TP)

6320/30-24G-500 2/3

Product Range	KNX
Number of Batteries	0
Design	
Surface Finishing	Untreated
	Glossy
Material	Thermoplastic
RAL Number	RAL 9016 - Traffic White
Color	studio white
Material Compliance	
RoHS Information	2CKA200000E5617
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	2CKA309999E9999
REACH Information	True - contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Environmental Ambient Air Temperature	Operation -5 +45 °C
Degree of Protection	IP20
Dimensions	
Product Net Width	90 mm
Product Net Height	84 mm
Product Net Depth / Length	33 mm
Product Net Weight	63 g
Built-In Depth (t ₂)	10 mm
Certificates and Declarations	
Declaration of Conformity - CE	2CKA100000E1521
Classifications	
ETIM 9	EC000672 - Touch sensor for bus system
eClass	V11.0 : 27143138
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

6320/30-24G-500 3/3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow User\ Operation \rightarrow Busch-triton @ \rightarrow 3/6\ fold\ Systems \rightarrow 3/6\ fol$

