6321/38-20-500 1/3



PRODUCT-DETAILS

6321/38-20-500

6321/38-20-500 triton 3/6gang MF/IR RTC



General Information	
Extended Product Type	

Product ID 2CKA006320A0052

EAN 4011395201329

Catalog Description 6321/38-20-500 triton 3/6gang MF/IR RTC

With integrated KNX bus coupler. With labelling field. Rocker switch left/right (switching/dimming/blind/value sender/light scenes/fan function). Master/slave configuration. With base-load operation. Control element with room thermostat function for triggering the heating, ventilation and fan-coil actuators. The controller is a constant room temperature controller for ventilator convectors (fan coils) in 2-pipe and 4-pipe systems and conventional heating or cooling systems. The fan stage can be switched manually or in automatic mode. Class of temperature controller 1

Contribution to space heating energy efficiency 1,0%.

and 4-pipe systems and conventio

Installation
Instructions and No document needed Manuals

Long Description

Mounting Type

Flush Mounted

6321/38-20-500

6321/38-20-500 2/3

Technical	
Data Sheet, Technical Information	2CKA001373B8838
Number of LEDs	1
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Number of Batteries	0

Design

Surface Finishing	Lacquered
	Matt
Material	Thermoplastic
Color	platinum

Material Compliance

RoHS Information	2CKA200000E5635
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	2CKA309999E9999
REACH Information	True - contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental

Ambient Air	Operation -5 +45 °C
Temperature	
Degree of Protection	IP20

Dimensions

Product Net Width	90 mm
Product Net Height	84 mm
Product Net Depth / Length	33 mm
Product Net Weight	98 g
Built-In Depth (t ₂)	10 mm
Screen Size	1.85 in

Certificates and Declarations

Declaration of	2CKA100000E1540
Conformity - CE	

Classifications

ETIM 9	EC001101 - Room temperature controller for bus system
eClass	V11.0 : 27143133
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Consumer

6321/38-20-500 3/3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow User\ Operation \rightarrow Busch-triton^{\circledast} \rightarrow 3/6\ fold$

