6321/38-24G-500 1/3



PRODUCT-DETAILS

6321/38-24G-500

6321/38-24G-500 triton 3/6gang MF/IR RTC



General Information	
Extended Product Type	6321/38-24G-500
Product ID	2CKA006320A0054
EAN	4011395201350
Catalog Description	6321/38-24G-500 triton 3/6gang MF/IR RTC
Long Description	With integrated KNX bus coupler. With labelling field. Rocker switch left/right (switching/dimming/blind/value sender/light scenes/fan function). Master/slave configuration. With base-load operation. Control element with room thermostat function for triggering the heating, ventilation and fan-coil actuators. The controller is a constant room temperature controller for ventilator convectors (fan coils) in 2-pipe and 4-pipe systems and conventional heating or cooling systems. The fan stage can be switched manually or in automatic mode. Class of temperature controller 1 Contribution to space heating energy efficiency 1,0%.

Installation	
Instructions and Manuals	No document needed
Mounting Type	Flush Mounted

6321/38-24G-500 2/3

Technical	
Data Sheet, Technical Information	2CKA001373B8838
Number of LEDs	1
Compatible Bus Systems	KNX (TP)
Product Range	KNX
Number of Batteries	0

Design	
Surface Finishing	Untreated Glossy
Material	Thermoplastic
RAL Number	RAL 9016 - Traffic White
Color	studio white

Material Compliance	
RoHS Information	2CKA200000E5637
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
REACH Declaration	2CKA309999E9999
REACH Information	True - contains substances > 0.1 mass percentage
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environmental	
Ambient Air Temperature	Operation -5 +45 °C
Degree of Protection	IP20

Dimensions	
Product Net Width	90 mm
Product Net Height	84 mm
Product Net Depth / Length	33 mm
Product Net Weight	98 g
Built-In Depth (t ₂)	10 mm
Screen Size	1.85 in

Certificates and Declarations	
Declaration of	2CKA100000E1541
Conformity - CE	

Classifications	
ETIM 9	EC001101 - Room temperature controller for bus system
eClass	V11.0 : 27143133
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

6321/38-24G-500 3/3

WEEE B2C / B2B Business To Consumer

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Building\ and\ Home\ Automation\ Solutions \rightarrow KNX \rightarrow User\ Operation \rightarrow Busch-triton ^{\circledcirc} \rightarrow 3/6\ fold$

